



Unlimited Rope Solutions

Rope Catalogue

2024 / 2025





LIROS Unlimited Rope Solutions

LIROS is now recognised as a world leader in the manufacture of high tech yachting ropes, kitesurf cords, paragliding lines and a wide range of industrial cordage. Latest production facilities enable LIROS to develop products for every customer requirement.

Special coatings developed by LIROS minimize the abrasion of high-quality fibre ropes and protect from UV-radiation. Thermal processes optimize the rope in terms of elongation and tensile strength. Our quality management systems ensure the highest level of quality for all LIROS customers.

For this reason LIROS produces innovative, sustainable and customer-optimised rope products – founded 170 years ago.

Sven Rosenberger

Karl Friedrich Rosenberger

Our company is certified and approved according to DIN EN ISO 9001 and DIN EN ISO 14001.

Production 100% Made in Germany.



Contents

LIROS Green Wave®	6	Theatre and Stage	58
Yacht Rope		Safety Line	61
XTReme	10	Arboriculture/Forest	65
Performance	15	Forest/Agriculture	66
Cruising	20	Offroad	67
Mooring	26	Industry	70
Anchoring	34	Barrier Rope	80
Dinghy	35	Traditional	81
Custom Performance	39	Natural Fibre Rope	83
Sailmaker	42	Technical Accessories	85
Shock Cord/Tie-down Attachment	45	Shop Displays	90
Selections in show-boxes	47	LIROS Promotion Material	92
Flightsport/Kite	51	Recommended Yachting Line Diameters	94
Flightsport/Paragliding	54	Recommended Mooring Line Diameters	95
Flightsport/Paragliding/Safety	56	Application Recommendation	96
Flightsport/Towing/Harness	57	Performance	97



LIROS – YOUR EXCELLENT PARTNER



Latest technology Essential for producing premium products



Laboratory Technical development of unique rope solutions



Quality control guarantees continuous quality



Logistics EDP-based warehousing for fast order processing

LIROS HSS

||||||| Heat Stretch System

LIROS HSS pre-stretch system uses exact heat treatment to guarantee the highest accuracy in any application.

LIROS LCS

■■■■■■■ LIROS Coating System

LIROS LCS is the best Protection against wear-and-tear and UV effects for technical ropes. LIROS LCS increases UV- and wear-resistance by up to 50%.



100% recyclable products. Natural fibres and single-origin synthetic fibres.

LIROS line optimization systems


Unlimited Rope Solutions!

Quality Made in Germany


Our LIROS customer service team has solutions for even the most demanding customers / retail, wholesale, or direct-to-industry. We'll provide all the dimensional sizing, working and breaking load information you need to choose the right LIROS product for the job.




Individual terminations




Tapered




Whipping




Pilot eye




Eye splice




Protective cover



Shackle




Sewn eye splice




Thimble




Continuous splice



Stripped eye splice



Leather



Friction Ring

In addition to common splicing and whipping, our experienced ropemakers specialise in fashioning and finishing of high-tech sheets, mooring lines and halyards. We can create the perfect individual rope for your specifications.

LIROS CUSTOMER SERVICE TEAM

Available monday to thursday 7:30am to 4:30pm and friday 7:30am to 1:00pm
+49 (0) 92 93 / 8002-0 or info@liros.com

For registered dealers the B2B dealer portal on our website www.liros.com is available 24/7.
Check warehouse availability and have instant access to the documents archive.



LIROS Green Wave®

Sustainable action and fair, environmental conscious management is one of the biggest challenges of our time. At LIROS it is our corporate philosophy – the LIROS Green Wave. It is at the same time a seal of approval, concept and binding mission statement for corporate action. The harmonisation of ecology and economy that takes responsibility in its entirety both for the environment and the population.

Production and consumption of energy has major ecological and social impacts. As a company we use energy as sparingly as possible whilst also using alternative sustainable and environmentally friendly techniques. LIROS aims to achieve climate neutrality in all areas of its business.

LIROS is certified according to **DIN EN ISO 14001:2015**. This demonstrates an effective environmental protection management system in all relevant divisions.



Photo: Paragliding World Cup

LIROS produces as an outdoor supplier for low environmental impact sports, for example, sailing, paragliding and kiting. As well as a supplier of extremely lightweight high strength componentry for the industry, LIROS has taken an active part in helping to reduce its CO₂ emissions.


LIROS Recycled Products

LIROS' recycled products allow for sustainable concepts, thereby reducing CO₂ and energy emissions and increasing resource conservation efficiency. In addition, new fields of application in environmental technology are constantly being developed. Our yarn suppliers guarantee the environmentally friendly recycling of old goods. We use raw materials in the form of R-PET for rope production in our newly developed products. For example, LIROS Green Wave Porto, or LIROS PES Cordage Green Wave.

LIROS uses GRS-certified R-PET yarn (high strength yarn made from 100% PET bottles). Every ton of recycled PET produces 1.5-2.0 tons less of CO₂ emissions than conventional polyester, a saving of around 70%.




LIROS GREEN WAVE



Reducing the Ecological Footprint

LIROS consistently pursues the goal of ensuring sustainable production for its partners and suppliers. As an example, the high strength fibers of Bio-based Dyneema.





LIROS Photovoltaics & Biogas

The entire company in Berg, Upper Franconia with its state of the art machinery is heated by the waste heat from a biogas reactor. An in-house photovoltaic system guarantees a completely CO₂-free power supply of the rope production with self-generated solar energy.

On sunny days the whole rope production is running with 100% photovoltaic energy from our roof top.



LIROS Electro mobility

Regional transport at Liros is carried out with an electric vehicle. By using the companies photovoltaic system the vehicle is completely climate neutral.





NEW

LIROS Green Wave Porto

00134

A very easy to handle mooring and anchor line manufactured in a core cover construction. Made from 100% recycle polyester, tear and abrasion resistant and will not harden. High stretch achieved through a special twisting construction.

- stretch >15%
- very easy to splice
- easy handling and UV stable
- tear and abrasion resistant



Ø mm	Breaking strength kg	Length of spool m
8	1450	200
10	2000	200
12	2600	200
14	3300	150
16	4400	100
18	4700	100
20	5600	100
22	8000	100

Colour



271
White-Black-Green

Cover

R-PET high twisted

Construction

Ø 8–10mm 16-plaited
Ø 12mm and up 20-plaited

Core

high-strength R-PET braid

LIROS GREEN WAVE

NEW

LIROS PES 3-strand Green Wave

01114

A classic rope for mooring and anchoring, very easy to splice, tear and abrasion resistant. 3-strand twist, made from 100% recycled Polyester.

- working stretch > 15%
- very easy to splice
- very strong and abrasion resistant
- heat-set
- good UV stability
- perfect for a lot of industrial applications

Ø mm	Breaking strength kg	Length of spool m
12	2300	200
14	3200	150
16	4500	100

Material

High Strength R-PET

Construction

3-strand, heat-set

Colour



271
White-Black-Green





LIROS XTReMe Technology

The LIROS XTR range delivers high quality watersports lines with optimised braiding constructions and best core-cover interaction for optimised grip, high abrasion resistance, minimal stretch as well as extreme breaking load.

1. Grip factor

The LIROS grip factor constitutes one of the most important decision factors for the professional sailor and helps the rigger to select the perfect line with ideal properties. The most diverse requirements in case of grip on winches and in stoppers is paramount in the LIROS XTR-Range. Grip factor is expected to improve during use.

3. Weight


The entire XTR range offers exceptional abrasion resistance and breaking loads at lowest weight. LIROS achieves this with LCS and with LIROS HSS as well as specially twined and coated covers. The LIROS Coating System (LCS) furthermore reduces water absorption up to 33%.

2. Abrasion resistance

LIROS XTR ropes captivate due to excellent abrasion resistance and deliver best results even under toughest conditions.

4. Stretch

The construction and core material essentially specify the stretch of a rope. LIROS XTR is optimised for lowest stretch and elasticity and transforms the wind power very efficiently into propulsion.





LIROS Control-XTR

02224

LIROS Control-XTR is a constantly developed line optimised for grip, combined with high abrasion and temperature resistance. For hard use.

- grip factor 10 (page 10)
- maximum grip under extreme winch and stopper conditions
- excellent abrasion resistance
- superior cover-core power transference
- low stretch

Technora®

The power of Aramid



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Cover

Technora® /
high-ten. Polyester

Construction

8 mm 24-plaited
10 mm and up 32-plaited

Core

Dyneema® SK99
12-plaited pre-stretched
with LIROS HSS and
LIROS LCS

Ø mm	Weight g/m	Weight cover g/m	Weight core g/m	Stretch %	Breaking strength kg	Length m
8	44	20	24	< 1,0	6250	200
10	60	27	33	< 1,0	8000	200
12	95	48	47	< 1,0	11200	200
14	131	60	71	< 1,0	14100	150
16	167	72	95	< 1,0	17500	100
18	211	109	102	< 1,0	20400	100
20	234	111	123	< 1,0	23500	100
22	270	135	135	< 1,0	27600	100
24	320	160	160	< 1,0	31500	100

Colours



019 Blue-Black



090 Green-Black



178 Red-Black



239 White-Black



LIROS Runner Vectran®-XTR

04008

LIROS Runner Vectran®-XTR is the rope with ultimate cover for minimal abrasion and high temperature conditions.

- grip factor 8 (page 10)
- XTREME abrasion resistance at high temperatures up to 200°C
- melt resistant cover
- superior cover-core power transference
- lowest stretch, top reliability
- extreme grip applications

Cover

100% Vectran®

Construction

32-plaited

Core

Dyneema® SK99
12-plaited
pre-stretched with LIROS
HSS and LIROS LCS

Colour



705 Beige NF

Ø mm	Weight g/m	Weight cover g/m	Weight core g/m	Stretch %	Breaking strength kg	Length m
6	31	16	15	< 1,0	2800	200
8	53	29	24	< 1,0	6250	200
10	62	29	33	< 1,0	8000	200
12	89	42	47	< 1,0	11200	200
14	144	71	73	< 1,0	14100	150
16	199	102	97	< 1,0	17500	100

Vectran™



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System



XTREME



LIROS Racer-XTR

02008

LIROS Racer-XTR offers an exceptional combination of heat-resistant hybrid fibres and high-tenacity Polyester. The extremely low-stretch, colour-treated Dyneema® SK78 core guarantees the best in breaking load and is perfect for cover stripping.

- working stretch < 1%
- lightweight
- perfect for extreme performance with stripped cover
- excellent abrasion resistance, even at high temperatures
- hybrid fibre prevents cover melting
- ideal interconnected cover-core
- multipurpose sheet and halyard rope
- very low stretch
- LIROS Heat Stretch System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
8	4700	53	200
10	6900	65	200
12	9900	93	200
14	13000	121	150
16	15200	156	100
18	18500	180	100
20	21700	222	100
22	24600	270	100
24	28000	320	100

Colours

-  419 Beige-Orange
- NEW**  262 Beige-Silver
-  421 Beige-Yellow
-  422 Beige-Burgundy
-  263 Beige-Steelblue

Cover 50% Vectran® / 50% Polyester
32-plaited

Construction 8 mm 24-plaited
10mm and up 32-plaited

Core Dyneema® SK78 with
XTR-Grip-Coating Silver



- NEW**  549 Beige-Black



LIROS D-Pro-XTR

01514

D-Pro-XTR is a 12-plaited braided Dyneema® line with highly durable XTR Grip Coating. Well-suited as a replacement for steel ropes and hard shackles. D-Pro-XTR is the ultimate line for applications that require the least stretch.

- XTREME high breaking load
- grip factor 3 (page 10)
- extremely low stretch
- very light weight
- easy to splice
- no water absorption
- easy to cover with Protect-XTR (see page 14)


Ø mm	Weight g/m	Stretch %	Breaking strength kg
------	------------	-----------	----------------------

NEW

2,5	3,5	< 1,0	700
3	5	< 1,0	1150
4	7	< 1,0	1500
5	13	< 1,0	3200
6	23	< 1,0	5600
8	35	< 1,0	7000
10	60	< 1,0	11000
12	72	< 1,0	15000
14	95	< 1,0	18000
16	131	< 1,0	22400
18	166	< 1,0	28000



Colour



205 Silver

Material Dyneema® SK99
Construction 12-plaited



LIROS D-Pro Static 01504

LIROS D-Pro Static is the only Dyneema® product with no creep. Ideal for any application where dimensional stability is critical (outhaul, backstay, dinghy shrouds). Also suited for static lines in industrial or other water sports applications.

- no creep Dyneema® DM20
- high breaking load with smallest diameter and lowest weight
- exceptionally easy to splice
- highly UV-stable, excellent abrasion resistance
- LIROS Coating System LCS


Ø mm	Weight g/m	Stretch %	Breaking strength kg
3	5	< 1,0	900
4	7	< 1,0	1230
5	13	< 1,0	2450
6	23	< 1,0	4050
8	35	< 1,0	5000
10	60	< 1,0	8500
12	72	< 1,0	11300



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Colour



205
Silver

Material

Dyneema® DM20

Construction

12-plaited


LIROS V-Plus-XTR 04007

V-Plus-XTR is made of 100% Vectran® with high tech XTR Coating. Perfect as a wire replacement or alternative to hard shackles. An ideal line for applications that require constant length, lowest stretch without creep also under load. Vectran® delivers extreme precision. Perfect as bolt rope for high performance sails.

- grip factor 7
- working stretch < 1%
- no creep
- XTReme low initial elongation
- high-tech XTR coating
- easy to splice
- heat resistant up to 200°C
- easy to cover with Protect-XTR

Ø mm	Weight g/m	Stretch %	Breaking strength kg
2	3	< 1,0	400
3	7	< 1,0	1100
4	10	< 1,0	1500
5	22	< 1,0	3000
6	32	< 1,0	5000
8	48	< 1,0	6800

Colours



188
Black

220
Transparent

Material

100% Vectran® with LCS Coating

Construction

12-plaited

LIROS LCS
LIROS Coating System

Vectran™



LIROS Slide Protect XTR

10148

LIROS Slide Protect-XTR provides a supplemental cover and protects against abrasion in turning blocks and fairleads. Slide Protect-XTR is not suited for protection in stoppers or on winches, the low cover grip factor delivers lowest friction.



LIROS HSS
Heat Stretch System
LIROS LCS
LIROS Coating System

- grip factor 3 (page 10)
- very easy to splice
- best abrasion resistance and cut resistance

Material

Dyneema® SK78 with XTR-Coating

Colours



542
White NF
674
Deep Black

Reference	Measurements mm	Cover mm	for rope Ø mm	Construction	Breaking strength kg	Length of spool m
10148-0506	5 x 1,6	0,8	3-6	24-plaited	800	25
10148-0810	9 x 1,7	0,9	5-10	48-plaited	1600	25
10148-1214	12 x 2,7	1,4	8-12	48-plaited	2500	25
10148-1624	19 x 3,7	1,9	14-22	48-plaited	5500	25

LIROS Grip Protect XTR

04500

LIROS Grip Protect-XTR covers lines, provides optimal abrasion protection and protects the rope on sharp edges. The high-grip surface of this cover delivers the best in power transference inside a halyard stopper.



- grip factor 10 (page 10)
- very easy to splice
- high cut resistance
- very high heat resistance up to 400°C

Material

Technora® dope dyed Black

Colour



188
Black

Reference	Measurements mm	Cover mm	for rope Ø mm	Construction	Breaking strength kg	Length of spool m
04500-0506	5,5 x 1,2	0,6	3-6	24-plaited	600	25
04500-0810	10 x 1,7	0,9	5-10	48-plaited	900	25
04500-1214	15 x 2,7	1,4	8-12	48-plaited	1800	25
04500-1624	23 x 3,2	1,6	14-22	48-plaited	3200	25



LIROS Racer-Hybrid

02026

LIROS Racer-Hybrid offers an exceptional combination of heat- and cut-resistant hybrid fibres and high-tenacity Polyester. The cover can be stripped with ease for weight reduction. LIROS Racer-Hybrid has a perfectly balanced cover-core ratio for maximum reliability and best breaking strength.

- working stretch < 1,5 %
- excellent abrasion resistance, even at high temperatures
- perfect for extreme performance with stripped cover
- lightweight
- ideal interconnected cover-core
- multipurpose sheet and halyard rope
- LIROS Heat Stretch System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
6	2900	25	200
8	4200	48	200
10	5500	65	200
12	8000	93	200
14	10500	121	150

Cover 50% Vectran® / 50% Polyester

Construction 6 mm 16-plaited
8 mm 24-plaited
10mm and up 32-plaited

Core Dyneema® XTR-Grip-Coating Silver

Colours



419
Beige-Orange



422
Beige-Burgundy



421
Beige-Yellow



262
Beige-Silver



263
Beige-Steelblue




549
Beige-Black



Vectran™

LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System



LIROS Racer Vision

02027

New High-Tech rope in a modern style. Simple stripping and easy to splice. Excellent retention forces on winches and rope stoppers. Perfect design with special abrasion resistant LIROS steelblue Polyester. Special XTR-Grip-Coating.

- working stretch < 1,5 %
- maximum breakload and low weight
- ideal for halyards, sheets and winch uses
- easy to splice
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
8	4200	53	200
10	5500	75	200
12	8000	96	200
14	10500	127	150

Cover Polyester high twisted

Construction 8 mm 24-plaited
10mm and up 32-plaited

Core Dyneema® with
XTR-Grip-Coating Silver

Colours



212
Steelblue-Blue



353
Steelblue-Green



704
Steelblue-Orange



707
Steelblue-Neon Yellow



774
Steelblue-Silver



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

PERFORMANCE




LIROS Racer

02001









Proven, durable Dyneema® rope with high breaking load and low stretch featuring a specially-engineered 32-plaited cover and coated Dyneema® SK78 fibre core. For halyards and sheets. Very suitable for winches.

- working stretch < 1,5%
- high breaking load, easy handling and non-kinking
- for halyards and sheets
- very good winch suitability
- LIROS Heat-Stretch-System



Ø mm	Breaking strength kg	Weight g/m	Length of spool m
6	2500	27	200
8	3800	51	200
10	5000	71	200
12	7200	85	200
14	9500	115	150
16	12600	144	100
18	15300	179	100

Colours

	010 Blue		171 Red
	086 Green		525 Black NF
	130 Navy		529 Silver NF
	150 Orange		542 White NF

Cover

Polyester high twisted

Construction

6–8mm 24-plaited
10mm and up 32-plaited

Core

Coated Dyneema® SK78 with additional cover plait



LIROS V-Force





04000

LIROS V-Force with high strength Vectran® fibre. Super low stretch, comparable to wire, extremely durable and abrasion resistant. Excellent holding strength in stoppers and cleats with specialised 32-plait cover, ideal for halyards and backstays.

- working stretch < 1%
- very low initial stretch
- ideal interconnected cover-core
- best stopper durability
- no creep

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
5	950	17	250
6	1400	24	200
8	2800	56	200
10	3700	80	200
12	5300	105	200

Colours

	423 Silver-Red
	424 Silver-Green
	445 Silver-Black
	593 Silver-Blue

Cover

Polyester high-twisted

Construction

3–5 mm 16-plaited
6–8 mm 24-plaited
10mm and up 32-plaited

Core

Vectran®, 8 mm and up with additional cover plait





LIROS Regatta 2000

02000

Very low-stretch line for halyards, spinnaker and genoa sheets. An extremely light and durable high-performance rope with abrasion resistant braided cover and inner cover. Specialised core of coated Dyneema® SK78.

- working stretch < 1,5%
- extreme break resistant, light and durable
- 30% more abrasion resistant than conventional Polyester
- LIROS Heat-Stretch-System

Cover Special Polyester high-twisted
Construction 2–3 mm 16-plaited
 4 mm and up 1:1 plaited
Core Coated Dyneema® SK78,
 8 mm and up with additional cover plait



Colours

	354 Steel-blue-Red		353 Steel-blue-Green		205 Silver
	212 Steel-blue-Blue		213 Steel-blue-White		228 White
	352 Steel-blue-Yellow		952 Steel-blue-Neon Orange		525 Black NF

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
2	270	3	250
2,5	390	5	250
3	550	7	250
4	800	11	250
5	1100	15	250
6	2500	25	200
8	3800	42	200
10	5000	61	200
12	7200	88	200
14	9500	132	150
16	12600	150	100
18	15300	180	100
20	18500	236	100
22	20000	282	100
24	23000	321	100

PERFORMANCE



LIROS Dynamic Plus

02004

Easy-handling, abrasion resistant line with low stretch, premium Polyester cover and Dyneema® SK78 core. Suitable for use as a highend sheet, or low-stretch halyard by advanced cruising sailors.

- working stretch < 2%
- kink-free, low-stretch sheets for cruiser-racers
- easy to splice
- LIROS Heat-Stretch-System

Colours

	228 White		232 White-Green		236 White-Red
	229 White-Blue				
	231 White-Yellow				

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
3	500	7	250
4	710	11	250
5	870	17	250
6	1200	21	200
8	2300	38	200
10	3100	69	200
12	4800	89	200
14	6500	119	150

Cover Polyester high twisted

Construction 3–5 mm 16-plaited
 6–8 mm 24-plaited
 10 mm and up 32-plaited

Core Dyneema® coated, 6 mm and up with additional cover plait



PERFORMANCE

LIROS Dynamic Color






02028

Easy-handling, abrasion resistant line with low stretch, premium Polyester cover and Dyneema® SK78 core. Suitable for use as a highend sheet, or low-stretch halyard by advanced cruising sailors.

- working stretch < 2%
- kink-free, low-stretch sheets for cruiser-racers
- easy to splice
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
3	500	7	250
4	710	11	250
5	870	17	250
6	1200	21	200
8	2300	38	200
10	3100	69	200
12	4800	89	200
14	6500	119	150

Colours

	021 Blue-White
	067 Yellow-White
	092 Green-White
	179 Red-White
	775 Dark Grey-White



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Cover

Polyester high twisted

Construction

3–5 mm	16-plaited
6–8 mm	24-plaited
10mm and up	32-plaited

Core

Dyneema® coated,
6mm and up with additional cover plait

LIROS Max Load System (MLS)

LIROS MLS crafted halyards and sheets for all popular boat sizes. Regatta ready, manufactured to exact LIROS standards. LIROS MLS with integrated shackle comes in a handy MLS mesh stow bag.

- Premium workmanship
- Product information see above



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System



Colours

	021 Blue-White		179 Red-White
---	-------------------	---	------------------

Halyard (Main, Genoa, Spi)

Reference	Ø mm	Length m	Attachment / halyard shackle	Breaking strength kg	Boat Size ft
02028-0830	8	30	pilot eye / spliced Wichard 81433	1800	22–29
02028-1035	10	35	pilot eye / spliced Wichard 81434	2400	30–36
02028-1240	12	40	pilot eye / spliced Wichard 81434	3800	37–42

Sheet (Spi, Genoa)

Reference	Ø mm	Length m	Attachment / soft shackle	Breaking strength kg	Boat Size ft
02028-0825	8	25	whipping / soft shackle	1800	22–36
02028-1025	10	25	whipping / soft shackle	2400	37–40
02028-1230	12	30	whipping / soft shackle	3800	40–42

NEW



LIROS D-Pro

01505

LIROS Heat-Stretch-System guarantees optimal breaking loads and stretch characteristics of this line. Excellent chafing resistance, light weight, and easy spliceability make this line irreplaceable in all sorts of applications on racing boats of any size. Perfect as a replacement for steel cabling in technical applications.

- working stretch < 1 %
- very high breaking load with small diameter and very low weight
- first choice for any application under extreme loads
- very spliceable
- highly UV stable and chafe resistant
- LIROS Heat-Stretch-System


Material Coated Dyneema® SK78

Construction 12-plaited, heat-set and coated

Colours



010
Blue



059
Yellow




086
Green



171
Red



205
Silver



228
White



674
Deep Black (2 and up)



Not certified for lifting loads and personal security!

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
1	195	0,9	100
1,5	230	1,3	100
2	410	1,8	100
2,5	580	3,5	100
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
9	7500	49	100
10	9000	60	100
12	11900	72	100
14	14500	95	100
16	19200	131	100



LIROS D-Pro Vision

01508

The new LIROS D-Pro Vision made of 100% Dyneema® SK78 with extremely high breaking loads at lowest weight! Best differentiation in all applications – whether as high-strength winch rope in industrial use or as universally useable watersports line. High UV-stability combined with best abrasion resistance and highest breaking loads at lowest weight guarantee best safety in practical use. First choice for replacing steel ropes in sports and industrial use.

- working stretch < 1 %
- very high breaking load with small diameter and very low weight
- first choice for any application under extreme loads
- very spliceable
- highly UV stable and chafe resistant
- LIROS-Heat-Stretch-System

Colours



019
Blue-Black



065
Yellow-Black



178
Red-Black

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
10	9000	60	100



Material
Coated Dyneema® SK78

Construction
12-plaited, heat-set and coated

PERFORMANCE



LIROS Herkules

00154







Very resistant, extremely versatile premium quality rope. Specially designed for sheets and control lines on yachts of every size. Very durable and low stretch, easily spliced to wire – heat set. Excellent grip on winch drums, exceptionally abrasion resistant cover. First choice for Cruising yachts with extremely high standards.

- working stretch < 5%
- very high quality line for the demanding Cruising yacht
- easy to splice and absolutely non-kinking
- extremely durable, even under hard winching conditions




Ø mm	Breaking strength kg	Length of spool m
4	400	250
5	650	250
6	800	200
8	1600	200
10	2500	200
12	3500	200
14	4500	150
16	5000	100
18	6300	100
20	7000	100
22	8000	100
24	9000	100

Colours

	228 White		232 White-Green
	229 White-Blue		236 White-Red
	231 White-Yellow		239 White-Black

Cover high-strength Polyester **Construction** 1:1 plaited **Core** high-strength Polyester plaited



LIROS Herkules Vision







01552

Fresh colours combined with our premium silver grey Polyester. Very resistant, extremely versatile, top quality line. Specially designed for sheets and control lines on yachts of every size. Very durable and low stretch – heat set. Excellent grip on winch drums, exceptionally abrasion resistant cover. First choice for Cruising yachts with extremely high standards.

- working stretch < 5%
- very high quality line for the demanding Cruising yacht
- very broad range of uses: sheet, halyard or control line
- easy to splice and absolutely non-kinking
- extremely durable, even under hard winching conditions


Ø mm	Breaking strength kg	Length of spool m
6	800	200
8	1600	200
10	2500	200
12	3500	200
14	4500	150
16	5000	100

Colours

	423 Silver-Red		445 Silver-Black
	424 Silver-Green		458 Silver-Orange
	432 Silver-Yellow		593 Silver-Blue



Cover high-strength Polyester dope dyed **Construction** 1:1 plaited **Core** high-strength Polyester plaited



LIROS Herkules Color

01550

Very resistant, extremely versatile premium quality rope. Specially designed for sheets and control lines on yachts of every size. Very durable and low stretch, easily spliced to wire – heat set. Excellent grip on winch drums, exceptionally abrasion resistant cover. First choice for Cruising yachts with extremely high standards.

- working stretch < 5%
- the full-colour alternative to LIROS Herkules with high quality spun-dyed Polyester cover

Colours



171
Red



010
Blue



059
Yellow



NEW

166
Rainbow



705
Beige NF



086
Green



188
Black



130
Navy



529
Silver NF

Ø mm	Breaking strength kg	Length of spool m
4	400	250
5	650	250
6	800	200
8	1600	200
10	2500	200
12	3500	200
14	4500	150
16	5000	100
18	6300	100
20	7000	100
22	8000	100
24	9000	100



Cover high-strength Polyester dope dyed

Construction 1:1 plaited

Core high-strength Polyester plaited



LIROS Top Grip

01540

The new generation of high quality Cruising sheets. LIROS Top Grip has been specially developed for use on all Cruising yachts up to 50 feet. Maximum grip on winch drums delivers great control and easy handling in all situations.

- working stretch < 5%
- perfect handling
- smooth, comfortable surface
- maximum grip
- best abrasion resistance
- very durable construction

Colours



229
White-Blue



232
White-Green



236
White-Red



239
White-Black

Ø mm	Breaking strength kg	Length of spool m
6	750	200
8	1350	200
10	2200	200
12	3000	200
14	4000	150



Cover Polyester grip fibre and high-tenacity, spun-dyed Polyester

Construction 1:1 plaited

Core high-strength Polyester plaited




LIROS Top-Cruising

00152

Very durable, kink-free, long-lasting sheet made of 100% high-tenacity Polyester. For use as mainsail, jib, and spinnaker sheets. Ideal for blue water sailing and long distances. Easy to splice – heat set.

- working stretch < 5%
- the classic sheet for sailing yachts of any size
- non-kinking, easy-handling line with abrasion resistant cover and high breaking load
- easy-to-splice multi-purpose line

Colours



Cover
high-strength Polyester

Ø mm	Breaking strength kg	Length of spool m
4	450	250
5	780	250
6	1100	200
7	1300	200
8	1800	200
10	2700	200
12	3200	200
14	3800	150
16	6100	100
18	6900	100
20	9700	100

Construction
Ø 4–8 mm 16-plaited
Ø 10mm and up 20-plaited

Core
high-tenacity braided Polyester


LIROS Top-Cruising-Color

01528

Very durable, kink-free, long-lasting sheet made of 100% high-tenacity Polyester. For use as mainsail, headsail and spinnaker sheets. Ideal for blue water sailing, long distances. Easy to splice – heat set.

- working stretch < 5%
- the full-colour alternative to LIROS Top-Cruising with high quality spun-dyed Polyester cover

Colours



Cover
spun-dyed Polyester

Construction
Ø 4–8 mm 16-plaited
Ø 10mm and up 20-plaited

Ø mm	Breaking strength kg	Length of spool m
4	450	250
5	780	250
6	1100	200
8	1800	200
10	2700	200
12	3200	200
14	3800	150



Core
high-tenacity braided Polyester



LIROS Allround


00151

Economical double-braid for universal use in industry and watersports. Low water absorption, easy to handle, abrasion resistant – heat set.


- working stretch < 8%
- handy, economical, winch-ready sheet
- cover construction with good abrasion resistance
- minimal water absorption, well-suited for yachts up to 40 feet

Ø mm	Breaking strength kg	Length of spool m
6	800	200
8	1400	200
10	2200	200
12	2600	200
14	3300	150

Colours



229
White-Blue
232
White-Green



236
White-Red

Cover

Polyester

Construction

Ø 6–8mm 16-plaited
Ø 10mm and up 20-plaited

Core

high-tenacity braided Polypropylene multifilament



LIROS Seastar

00162 / 00172 / 00173

High quality, grippy Polyester sheet with exceptionally soft, easy to grip cover – heat set. Classic design, available in eight different colours with LIROS blue and gold flecks.

- working stretch < 6%
- soft, easy-to-handle, braided line
- salt water- and abrasion-resistant colours
- easily distinguishable colours help differentiate lines on deck

Ø mm	Breaking strength kg	Length of spool m
5	300	250
6	520	200
8	1000	200
10	1900	200
12	2400	200
14	2900	150
16	3400	100
18	4300	100

Colour 00162



228
White

Colour 00173



546
Hemp NF

Colours 00172



010
Blue
086
Green
130
Navy



171
Red
188
Black

Cover

Polyester yarn matt

Construction

Ø 5mm 8-plaited
Ø 6–8mm 16-plaited
Ø 10–12mm 20-plaited
Ø 14mm and up 24-plaited

Core

high-tenacity braided Polyester

NEW



LIROS Standard

01082

Economical and soft sheet with easy to grip spun Polyester cover – heat set.

- working stretch < 8%
- soft and easy to grip
- all-purpose sheet

Ø mm	Breaking strength kg	Length of spool m
6	500	200
8	1000	200
10	1600	200
12	2500	200
14	3000	150

Colours



Cover

matt Polyester yarn

Construction

Ø 6–12 mm 16-plaited
Ø 14mm and up 20-plaited

Core

high-tenacity braided Polypropylene



LIROS Nautic

01072


Soft, very light, and easy-to-handle spsheet for dinghies or small keelboats. Can also be used as water-ski rope or towline. Spun-dyed, multi-purpose floating line. Round-woven, UV-stabilised, durable Polypropylene multifilament. **1–5 mm without flecks.** 6–16 mm with flecks in blue/gold.

- working stretch < 12%
- very lightweight
- easy to handle
- floatable
- UV-stabilised



Ø mm	Breaking strength kg	Length of spool m
1	30	500
1,5	38	500
2	70	500
3	140	500
4	280	500
5	390	250
6	550	200
8	900	200
10	1230	200
12	1700	200
14	2000	150
16	3700	100

Colours Ø 1-5 mm (NF)



Colours Ø 6-16 mm




Material

Polypropylene multifilament

Construction

8-plaited



LIROS Reflecta

02100

High-quality safety line for recovering individuals, for use with rescue systems or rigid danbuoys. Floating line with reflective fleck, making the rope easily visible under torch or spotlight illumination.

Ø mm	Breaking strength kg	Length of spool m
6	550	200
8	900	200

- working stretch < 12%
- reflective flag
- round
- floats

Colour



059
Yellow

Material

Polypropylen multifilament with reflective fleck

Construction

8-plaited



LIROS Prestretch

00121 / 00122

Pre-stretched for low elongation. Use for wire halyard leaders, control lines on dinghies and small boats – heat set. Perfect for many industrial applications.

- working stretch < 4%
- low stretch, inexpensive Polyester halyard for smaller boats and traditional Cruising yachts
- 3-strand, very easy to splice (Ref. 00121)

Reference	Ø mm	Breaking strength kg	Length of spool m
00121	4	420	250
	5	600	250
	6	820	200
00122	8	1400	200
	4	420	250
	5	580	250
	6	800	200

Colour 00121



228
White

Colours 00122



188
Black



228
White

Material

Polyester heat-set

Construction

00121 twisted 3-strand

00122 8-plaited





LIROS Super Yacht Mooring 01300




LIROS Super Yacht Mooring is a mooring line developed for superyachts up to 200 feet. Flexible core provides the best in safety, while the specialised LIROS cover delivers premium comfort. Our high end LIROS version with eye splice and protective leather chafing guard available upon request in individual lengths.


- working stretch > 15%
- ultimate in safety
- extremely easy to handle
- highly abrasion resistant LIROS Leather Guard eye splice in brown or black

Cover Polyester high-twisted dope dyed
Construction 24-plaited, coated
Core high-tenacity braided Polyester



Colours

	130 Navy
	188 Black
	308 Dark Grey



Abrasion testing in LIROS labs

Reference	Ø mm	Boat size * ft	Breaking strength kg	Weight g/m
01300-2400	24	70 to 90	11500	400
01300-2800	28	up to 120	15900	580
01300-3200	32	up to 150	19800	740
01300-3600	36	up to 180	26000	950
01300-4000	40	up to 200	32800	1150
01300-4400	44	up to 220	38500	1420
01300-4800	48	up to 250	46000	1700
01300-5200	52	up to 280	53500	1980

* for yachts heavier than average, choose the next larger diameter



Leather chafing guard



100% hand-sewn, Made in Germany



Premium whipping



LIROS Handy-Elastic

00136 / 00137

The top performer in LIROS tests. High-stretch, extremely abrasion resistant mooring line, towline or anchor line. Specially designed with high elastic fibres. Can be used for shock absorption in extreme settings.

- *working stretch > 20%*
- *very easy to splice*
- *highly elastic and highly UV-stable*
- *extremely abrasion resistant*
- *very easy to handle*
- *very low-noise (when pulsating) under varying loads*
- *up to 40mm diameter available upon request*

Ø mm	Breaking strength kg	Length of spool m
8	1600	200
10	2500	200
12	3900	200
14	4800	150
16	6000	100
18	8500	100
20	9900	100
22	10600	100
24	12000	100

Colours 00136



142
Navy-Yellow



188
Black



942
Dark Grey-Black-Red

Cover

high-strength Polyamide

Construction

1:1 plaited

Core

high-elastic braided Polyamide



Colour 00137



289
White-Black-Red



LIROS Handy-Elastic pre spliced

Reference 00136/00137	Ø mm	Length m	Eye splice cm
-1006	10	6	40
-1010	10	10	40
-1015	10	15	40
-1206	12	6	40
-1210	12	10	40
-1215	12	15	40
-1406	14	6	40
-1410	14	10	40
-1415	14	15	40

Reference 00136/00137	Ø mm	Length m	Eye splice cm
-1606	16	6	40
-1610	16	10	40
-1615	16	15	40
-1806	18	6	40
-1810	18	10	40
-1815	18	15	40



LIROS splices are guaranteed up to 80% of the stated linear breaking load!



LIROS Porto

00133

Very easy to handle 100% Polyester mooring or anchor line. Extremely strong and abrasion resistant, will not stiffen up. Special twist construction for high stretch.

- working stretch > 15%
- very easy to splice
- highly UV-stable
- high strength and excellent abrasion resistance


Cover
Polyester high twisted

Construction
Ø 8–10mm 16-plaited
Ø 12 mm and up 20-plaited

Core
high-strength Polyester braid

Ø mm	Breaking strength kg	Length of spool m
8	1650	200
10	2300	200
12	2900	200
14	3700	150
16	4900	100
18	5300	100
20	6300	100
22	8900	100

Colours



LIROS Porto pre spliced


Reference	Ø mm	Length m	Eye splice cm
00133-1006	10	6	40
00133-1010	10	10	40
00133-1015	10	15	40
00133-1206	12	6	40
00133-1210	12	10	40
00133-1215	12	15	40
00133-1406	14	6	40
00133-1410	14	10	40
00133-1415	14	15	40
00133-1606	16	6	40
00133-1610	16	10	40
00133-1615	16	15	40
00133-1806	18	6	40
00133-1810	18	10	40
00133-1815	18	15	40

Reference	Ø mm	Length m	Eye splice
00133-1030	10	30	S/S thimble
00133-1230	12	30	S/S thimble
00133-1430	14	30	S/S thimble
00133-1630	16	30	S/S thimble



LIROS splices are guaranteed up to 80% of the stated linear breaking load!

Colours





LIROS Holiday

01083

A textured, grippy but soft mooring line for travelling. Light as a feather for low water absorption. Good abrasion resistance for sailing trips. Kink free for easy mooring.

- working stretch < 15%
- easy splicing
- light and floatable
- very good price-performance ratio

Colour



381
Black-Silver



Ø mm	Breaking strength kg	Length of spool m
10	1500	200
12	2100	200
14	2800	150
16	3200	100

Material

spun dyed Polypropylene multifilament



Construction

16-plaited

LIROS Bumperline

01079

Premium square-braided fender line. Smooth material lays flat against topsides. Soft and easy to handle. Spliced attachments on both ends. 100% UV stabilised Polypropylene multifilament. Length between splices: 2,5m, diameter: 12mm.

- pliable
- lays cleanly against topsides
- soft and easy to handle
- low water absorption
- floatable

Colour



130
Navy

LIROS Flat-Elastic

00140

Newly designed mooring line without a core. Exceptional handling, durable, tear and abrasion resistant. Space saver, and very flexible.

- working stretch > 20 %
- highly elastic and UV-stable
- very easy to splice

Cover

high-strength Polyamide

Construction

1:1 plaited

Colour



188
Black

Reference	Ø mm	Length m
01079-5001	50	5
01079-5002	50	7,5



Material

spun dyed Polypropylene multifilament

Construction

8-plaited square braiding



Ø mm	Breaking strength kg	Length of spool m
12	2400	150
14	3400	100
16	4200	100





LIROS Squareline-PES

01047 / 01049

Super pliable, easy handling square-braided mooring or anchor line of 100% high-tenacity Polyester. 100% kink-free, easy to splice and easily joined to chain.


- working stretch > 15%
- soft and easy to handle, extremely UV-stable
- smooth, comfortable feel
- non-kinking and extremely abrasion resistant
- easy to splice



Material
high-strength Polyester

Construction
8-plaited Octoplaît

Colour 01047



Colours 01049



Ø mm	Breaking strength kg	Length of spool m
10	2000	200
12	2400	200
14	3800	150
16	4700	100
18	5800	100
20	7600	100
22	8600	100
24	10700	100
26	13700	100
28	15000	100

LIROS Squareline-PP

01078 / 01079 / 01080

Very light and easy-to-handle mooring line, land line, or towing line. High-strength, floating, UV-stabilised.

- working stretch > 15%
- floats
- low water absorption




Construction
8-plaited Octoplaît

Material
high-strength Polypropylene multifilament

Colour 01078



Colours 01079



Colour 01080



*Available up to 28mm.

Ø mm	Breaking strength kg	Length of spool m
12	2100	200
14	2700	150
16	3400	100
18	4000	100
20	5000	100

LIROS Fender Line

01580

- pair of premium fender lines
- eye splice (15cm) on one end
- 1,5m customized or 100m reels without eyes



Reference	Ø mm	Length m	Breaking strength kg	Eye cm
01580-0802	8	1,5	900	15
01580-0800	8	100	1000	–
01580-1002	10	2	1500	15
01580-1000	10	100	1500	–



Colour



Material high-tenacity black Polyester



LIROS Moorex 12

00132

Very pliable, easy to handle, high-stretch mooring line. Hollow braided, very easy to splice. 12-plaited high-tenacity Polyester.

- *working stretch > 15%*
- *economical braided LIROS mooring line*
- *very smooth and easy to handle*
- *high stretch*
- *easy to splice*

Ø mm	Breaking strength kg	Length of spool m
10	2400	200
12	3000	200
14	4000	150
16	4600	100
18	5300	100
20	7200	100

Colours



130
Navy



188
Black



Material

high-strength Polyester

Construction

12-plaited



LIROS Moorex 12 pre spliced

Reference	Ø mm	Length m	Eye splice cm
00132-1006	10	6	40
00132-1010	10	10	40
00132-1015	10	15	40
00132-1206	12	6	40
00132-1210	12	10	40
00132-1215	12	15	40
00132-1406	14	6	40
00132-1410	14	10	40
00132-1415	14	15	40

Reference	Ø mm	Length m	Eye splice cm
00132-1606	16	6	40
00132-1610	16	10	40
00132-1615	16	15	40
00132-1806	18	6	40
00132-1810	18	10	40
00132-1815	18	15	40



LIROS splices are guaranteed up to 80% of the stated linear breaking load!

Colours



130
Navy



188
Black



LIROS Polyester Rope 00111 / 01110


Classic, very easy to splice, high strength, abrasion resistant rope for mooring and anchoring. 3-strand made of 100% Polyester. Heat-set. According to **DIN EN ISO 1141** standards (previously DIN EN 697, DIN 83331), heat set.

- working stretch > 15%
- very easy to splice
- extremely strong and abrasion resistant
- heat-set
- highest UV stability
- perfect for a lot of industrial applications



Ø mm	Breaking strength kg	Length of spool m
3	280	250
4	400	250
5	600	250
6	800	200
8	1400	200
10	2000	200
12	2600	200
14	3600	150
16	5000	100
18	6000	100
20	7000	100
22	9000	100
24	10500	100
30	14800	100


Colour 00111



Material
high-strength Polyester

Construction
3-strand, heat-set

Colours 01110



LIROS Polyester Rope pre spliced


Reference	Ø mm	Length m	Eye splice cm
00111-1006	10	6	40
00111-1010	10	10	40
00111-1015	10	15	40
00111-1206	12	6	40
00111-1210	12	10	40
00111-1215	12	15	40
00111-1406	14	6	40
00111-1410	14	10	40
00111-1415	14	15	40
00111-1606	16	6	40
00111-1610	16	10	40
00111-1615	16	15	40

Reference	Ø mm	Length m	Eye splice
00111-1030	10	30	S/S thimble
00111-1230	12	30	S/S thimble
00111-1430	14	30	S/S thimble
00111-1630	16	30	S/S thimble



LIROS splices are guaranteed up to 80% of the stated linear breaking load!

Colour 00111






LIROS Polyamide Rope

00110

Classic mooring line with high elasticity. 3-strand twist for easy splicing. High strength and excellent abrasion resistance. 100% heat-set Nylon, according to **DIN EN ISO 1140** (previously DIN EN 696, DIN 83330), heat set.

- working stretch > 20%
- very easy to splice
- extremely durable and abrasion resistant
- UV stabilised
- perfectly suited for multiple industrial uses

Colours



Material high-strength Polyamide

Construction 3-strand, heat-set

Ø mm	Breaking strength kg	Length of spool m
4	380	250
5	600	250
6	900	200
8	1440	200
10	2400	200
12	3300	200
14	4400	150
16	5600	100
18	7000	100
20	8140	100
22	9800	100
24	11800	100
30	17400	100
32	19600	on request
36	24400	on request



LIROS Lirolen

01120 / 01123 / 01126

All-purpose, floating 3-strand rope. Easy to splice, stays pliable even after extensive usage. According to **DIN EN ISO 1346** (previously DIN EN 699, DIN 83332)

- 01120:** Polypropylene multifilament, heat-set, white
- 01123:** Polypropylene multifilament spun dyed, heat-set
- 01126:** Polypropylene multifilament spun dyed, heat-set

- working stretch > 15%
- easy to splice
- economical, allround line
- low water absorption
- floatable
- perfect for many industrial applications




Ø mm	Breaking strength kg	Length of spool m
4	280	250
5	425	250
6	600	200
8	1000	200
10	1500	200
12	2120	200
14	2800	150
16	3750	100
18	4500	100
20	5600	100

Colour 01120



Colours 01123



Colour 01126



Material
high-strength Polypropylene multifilament

Construction
3-strand, heat-set




LIROS Handy-Anchor 01320

High quality anchor line with lead weight built into the last ten meters. Can be used without chain, especially easy to handle and stow. Available in 20, 30 and 40m lengths, with spliced S/S-thimble and whipping. 100% Polyester abrasion and UV-resistant. Comes in handy, blue LIROS kitbag.

- can be used without chain
- super easy to handle
- very simple to stow
- attractive LIROS kitbag



Colour



229 White-Blue



All lengths have 10 m of integrated lead weighting and steel thimble



Ø mm	Breaking strength kg	Length of spool m	Weight kg
10	1500	20	3,4
10	1500	30	4,2
10	1500	40	4,9
12	2200	20	4,1
12	2200	30	5,0
12	2200	40	6,3
14	3100	40	8,5
16	4000	40	10,8
16	4000	50	13,5


Cover Polyester
Construction 20-plaited
Core Polyester, lead (10 m from S/S thimble)

LIROS Winch-Master W1322

Similar to LIROS Handy-Anchor, but optimised to withstand windlass usage.

- completely with lead core
- attractive LIROS kitbag

Colour



228 White



Ø mm	Breaking strength kg	Length of spool m	Weight kg
12	1500	30	4,5
12	1500	40	5,9
12	1500	50	7,4
14	2200	40	11,0
14	2200	50	14,2
16	3100	40	12,9
16	3100	50	16,1

Cover Polyester
Construction 12 mm 16-plaited
 14 mm and up 20-plaited
Core Polyester, lead



LIROS Magic XTR

01513

LIROS Magic XTR is ideal for use in dinghies and multihulls. Superior high grip, extremely durable cover. Perfect in cleats. The professional's choice.

- working stretch < 1%
- grip factor 9 (page 10)
- removable cover for top performance
- superior abrasion resistance – combo-cover (twisted Technora®/Dyneema®)
- best cover-core attachment
- very low stretch, highest breaking load
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Length of spool m
4	620	100
5	1400	100
6	1800	100



Colours



231
White-Yellow



239
White-Black

Cover

Technora® / Dyneema® Mix

Construction

4–5 mm 16-plaited
6 mm 24-plaited

Core

Dyneema® SK78 with LIROS XTR Grip Coating



LIROS Magic Control XTR

02024

Maximum grip for exact control of your dinghy. High tech materials provide highest reliability and enable precise manoeuvres, when it counts.

- working stretch < 1,0%
- coated core
- very resistant and handy
- minimum stretch
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Length of spool m
4	1100	100
5	1450	100
6	2800	100



Colours



090
Green-Black



239
White-Black



178
Red-Black



652
Neon Yellow-Black

Cover

Technora® / Polyester

Construction

4–5 mm 16-plaited
6 mm 24-plaited

Core

Dyneema® SK78 silver with LIROS XTR Grip Coating



LIROS Magic Pro

01507

LIROS Magic Pro combines all of the best characteristics with extreme low stretch. Outstanding block performance, enabling ultra-fast manoeuvres. The core is coated and specially treated with LIROS Heat-Stretch-System. The cover is made of a special Polyester grip fibre / spun-dyed Polyester mix for optimal control and perfect handling in manoeuvres.

- working stretch < 1,5%
- grip factor 9 (page 10)
- precise cover construction for excellent hold in cleats and winches
- ideal for cover-stripping
- LIROS Heat-Stretch-System for lowest stretch

Ø mm	Breaking strength kg	Length of spool m
3	450	100
4	620	100
5	1250	100
6	1800	100
8	3000	100

Colours



Cover

Polyester grip fibre / spun-dyed Polyester mix

Construction

16-plaited

Core

Dyneema® SK78 with coloured LIROS XTR Grip Coating



LIROS Magic Edge

01502

Robust and handy low-stretch performance rope for all applications to regatta and advanced dinghy sailing boats. Best abrasion resistance due to high tech and tight cover braid.

- working stretch < 1,0%
- coated core
- resistant and handy construction
- low elongation
- 1,5–2mm single-coloured
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Length of spool m
1,5	125	100
2	250	100
3	420	100
4	580	100
5	1050	100
6	1800	100
7	2300	100

Colours



Cover

Spun dyed Polyester

Construction

1,5–5mm 16-plaited
6mm and up 1:1 plaited

Core

Dyneema® SK78 silver with LIROS XTR Grip Coating



LIROS Magic Race




02016

Extremely low stretch, compact, and abrasion resistant braid with high-strength Dyneema® core.

- working stretch < 1,5%
- highly UV resistant
- low stretch, high grip

Ø mm	Breaking strength kg	Length of spool m
2	270	100
2,5	390	100
3	550	100
4	800	100
5	1100	100

Colours



Cover

special high-twisted Polyester

Construction

2–3 mm 16-plaited
4 mm and up 1:1 plaited

Core

Dyneema® SK78 coated




LIROS DynaSoft

02055

LIROS DynaSoft combines the best grip, the lightest weight, and the lowest stretch. Combination braid of high-strength Polyester grip fibres and Dyneema®. Almost kink free rope, which has been achieved through thermal treatment of the rope. Ideal for dinghy sheets and regatta halyard leads.

- working stretch < 2%
- heat-set
- high grip
- extremely flexible
- excellent handleability
- limited suitability on winches
- LIROS Heat-Stretch-System for lowest stretch

Ø mm	Breaking strength kg	Length of spool m
7	1200	100
9	2000	100



Colours



Material

Ideal hybrid of Dyneema® SK78 and Polyester grip fibres

Construction

8-plaited with core



LIROS Magic Sport

01517


Technical high-grade, universally useable line in striking Neon-Design for dinghies and small keel boats. Very abrasion resistant core in cleats, low stretch due to heat-set Polyester core.

- working stretch < 5%
- very abrasion resistant
- high visibility
- low stretch




Ø mm	Breaking strength kg	Length of spool m
2	95	100
3	185	100
4	550	100
5	850	100
6	1000	100

Colours



781
Neon Yellow-White
771
Neon Yellow-Silver



417
Neon Yellow-Pink
773
Neon Yellow-Blue

Cover

spun dyed Polyester

Construction

16-plaited

Core

high-strength Polyester

LIROS Magic Sheet

01506

LIROS Magic Sheet has been specially developed for use as main and jib sheets on dinghies, sports boats, and catamarans. Polyester grip fibres provide best cover-core attachment and perfect grip for optimal control in any situation.

- working stretch < 8%
- great in turning blocks, fastest manoeuvres
- very compact non splice construction

Ø mm	Breaking strength kg	Length of spool m
7	970	100
9	1500	100

Cover

Polyester grip fibre / spun-dyed Polyester mix

Construction

16-plaited

Core

Polypropylene high-strength plaited

Colours



404
White-Silver
405
White-Marine



406
White-Orange
428
White-Pink



LIROS Magic Surf

The LIROS Magic Surf is specially designed for wind surfing and enables exact setting of the sail tension. 03000-0380 is suitable for all kinds of clutches. 00148-0419 enables extreme grip on sensitive clutches and at higher stress on systems with ratchet.

- working stretch < 1%
- extremely low stretch

Reference	Ø mm	Breaking strength kg	Length of spool m
03000-0380	3,8	1000	100
00148-0419	4,2	800	100



Colour



228
White

Material Dyneema® SK 78, pre-stretched

Konstruktion 3,8 mm 16-plaited
4,2 mm 8-plaited



LIROS Spi Pro

02049-0000

Very light, high quality, individually produced tapered spinnaker sheet with Dyneema® SK78 core for extremely low stretch and high strength. Minimal water absorption.

- Individual customisation available for any boat
- tailor-made for long working life
- lowest stretch and water absorbency
- premium spun Polyester for optimal grip
- available in diameters from 3 – 12 mm
- length, diameter, and colour customised to your specifications
- lowest weight
- available with eye splice

Cover

thick end – high-grip matt Polyester with Dyneema® SK78 / tapered end – 100% Dyneema® SK78


Core

braided Dyneema® SK78

Also available as
Opti-Design
6-9-6 mm in lengths of
1,5 - 2,5 - 3 m available.
Reference: 02042-0100




Colours



Required order specifications:

1. Ø thick end
2. length thick end
3. Ø tapered end
4. length tapered end
5. colour



Available Ø 02049 [mm] / Breaking strength tapered end [kg]:

5 – 3 / 480	10 – 4 / 780	8 – 6 / 2000
6 – 3 / 480	8 – 5 / 950	9 – 6 / 2000
6 – 4 / 780	9 – 5 / 950	10 – 6 / 2000
8 – 4 / 780	10 – 5 / 950	12 – 6 / 2000
9 – 4 / 780	12 – 5 / 950	12 – 8 / 3000



LIROS Spi

02049


Very light and high quality spinnaker sheet with Dyneema® SK78 core for optimal grip, low stretch and high strength. Minimal water absorption.

- working stretch < 3%
- premium spun Polyester for optimal grip
- lowest stretch
- light weight

Ø mm	Breaking strength kg	Length of spool m
5	650	100
6	800	100
8	1000	100
10	1900	100



Colours




Cover

high-grip matt Polyester with Dyneema® SK78

Core

Dyneema® SK78 plaited










LIROS Soft Shackle

Fastening sheets, shackle halyards, fix blocks – the LIROS XTR Soft Shackle is the solution! 100% made of high-strength fiber Dyneema® SK78, replaces heavy metal shackles on deck. Easy and fast opening, thanks to the blue „LIROS ribbon“ with breaking strength information.

- No damages on deck or risk of injuries when operating by flapping metal parts
- suitable for many applications in sectors industry, offroad and outdoor
- 10x lighter than steel shackles at same breaking strength
- Easy and intuitive handling
- self-locking construction under load
- easy to open after use with high loads
- safety factor 2:1



Colours

	010 Blue		171 Red		228 White
	059 Yellow		205 Silver		674 Deep Black
	NEW 086 Green				

Material Dyneema® SK78

Reference	Breaking strength t	Colour	SWL** t	A Material Ø mm	B Final Ø app. mm	C Inner length mm
00146-0066	1	228 White*	0,5	4	6	65
00146-0090	1,5	674 Deep Black	0,75	5	9	90
00146-0069	2	171 Red*	1	6	12	120
00146-0070	4	010 Blue*	2	8	13	135
00146-0071	6	059 Yellow*	3	9	15	150
00146-0072	8	086 Green	4	10	19	150
00146-0073	10	674 Deep Black	5	12	20	190

* All sizes also available in deep black or silver!
 ** SWL = Safe Work Load



Not certified for lifting loads and personal security!




LIROS Taper Pro

02010

LIROS Taper Pro is the ideal line for latest generation of head-sail furlers. This high-strength Dyneema® line offers a smooth transition from thick to thin for optimal handling. The thick cover provides excellent grip, while the thin end enables easy rolling, even under heavy load with small diameter furlers. Perfect as a low-stretch halyard for boats from 25 – 35 feet.

- working stretch < 1,5%
- optimum grip on winches
- easy reefing, safe manoeuvres
- perfect solution for tapered halyards

Colours



Cover high-tenacity Polyester

Construction 1:1 plaited

Core Dyneema® SK78 with additional cover plaiting

Reference	Ø mm	Breaking strength kg	Length with tapering m
02010-0900	9–6	2300	from 9mm (20m) to 6mm (10m) / 30m
02010-1100	11–8	3200	from 11 mm (20m) to 8mm (15m) / 35m



LIROS D-Loop


Textile slings made of high strength Dyneema® SK99 provides various options for transferring loads. Maximum weight savings. Replaces heavy steel fittings. Ideal combination with low-friction rings, blocks and shackles. LIROS D-loops can be used in three variants: single, double and looped.

- working stretch < 2%
- maximum breakload at lowest weight
- LIROS Heat-Stretch-System
- round and safe

Colour




Application examples



single

double

looped



Material Dyneema® SK99

Construction 16-plaited, coated

Reference	A Material Ø mm	B Stretched length mm	SWL* single t	SWL* double t	SWL* looped t
00146-0230	4	100	0,6	1,2	0,48
00146-0231	7	100	1,1	2,2	0,88
00146-0232	8	130	1,6	3,2	1,28
00146-0234	10	170	2,5	5	2
00146-0235	10	200	2,5	5	2



Not certified for lifting loads and personal security!

*SWL = Safe Work Load



LIROS AntiTorsion EVO

11442

Proven, ideal replacement for cable forestays.

- working stretch < 1 %
- stiff, reinforced with braided monofilament inner cover
- high-strength Aramid core for extremely low-stretch and high breaking load
- non-splicing
- available in custom lengths

Colour



Ø mm	real Ø mm	Breaking strength kg
6	7,0-7,3	1300
8	9,6	3300
10,5	10,5	4000
11	11,3	4100
13	13,15	5000
16,5	16,0	8500

Cover

Polyester

Construction

16-plaited

Core

Aramid with braided monofilament


LIROS Leachline

01046

Compact, braided, shape-retaining leach line for sailmakers.

- round
- compact
- minimal shrinkage

Colour



Ø mm	Length of spool m
4	250
4,5	250
5	250
5,5	250
6	200
7	200
8	200

Cover

low-shrink Polyester

Construction

16-plaited

Core

Polyester


LIROS Lazy Jack

01532

New compact construction made of special high twisted Polyester. The very smooth and abrasion resistant surface protects the sail when dropping. The wide hollow braid is very easy to splice. Specially designed for use as Lazy Jack line.

- round and lightweight
- extremely UV-resistant and abrasion resistant

Colour



Material

special high twisted Polyester spun dyed

Construction

12-plaited without core

Ø mm	Breaking strength kg	Length of spool m
4	500	250
6	1100	200
8	2200	200





LIROS LSP Furler Line

Specially designed Furler Line with cover-core construction for use in all common furling systems. Abrasion resistant and UV-stable due to high quality Polyester cover. To manufacture endless spliced furling lines please use LIROS 00154 Herkules or LIROS 00152 Top-Cruising.

- *Stretch < 5%*
- *High resistance to bending*
- *Abrasion resistant and UV-stable*

Reference	Ø mm	Length m	Breaking strength kg
01546-0801	8	20	1700
01546-0802	8	25	1700
01546-1001	10	25	2700
01546-1002	10	28	2700
01546-1201	12	40	3200



Colour



239
White-Black

Cover

Polyester

Construction

8 mm 20-plaited
10–12mm 24-plaited

Core

Polyester



LIROS Webbing Dyneema®

00186

Premium webbing, low-stretch and high breaking strength.

- *lowest stretch*
- *very abrasion resistant*
- *no water absorption*
- *extremely UV resistant*

Ø mm	Breaking strength kg	Length of spool m
25	1800	50



Colour



228
White

Material

Dyneema® SK78



LIROS Magic Sail


01512

LIROS Magic Sail is ideal for sailmakers. Extremely shrink-resistant, round and compact for easy processing.

- minimal shrinkage
- good dimensional stability

Ø mm	Breaking strength kg	Length of spool m
3	185	500
4	320	500
5	680	250

Colour



236
White-Red



Cover

Polyester

Construction

2-5 mm 16-plaited
6 mm 1:1 plaited

Core

low-shrinkage Polyester



LIROS Bolt Rope

00124

Premium sailmaker's bolt rope. 3-strand, high-strength, low-shrink Polyester in white with black marker.

- round
- compact
- minimal shrinkage

Ø mm	Length of spool m
6	200
7	200
8	200
9	200
10	200

Colour



228
White




Material

low-shrinkage Polyester

Construction

3-strand



LIROS Safety Netting

02040-0001-228

Premium knotted safety netting of 2 mm white, braided Polyester with reinforced edging.

- mesh openings approx. 45mm
- netting width 60cm
- 50m lengths



Detail view



LIROS Shock Cord


00190

Our high-elasticity shock cord with the best in stretch characteristics. Braided out of abrasion resistant Polyester in solid colour or white with blue-gold mark yarn.


- round, abrasion-resistant construction
- also available in industrial bulk quantities
- Made in Germany

Ø mm	Breaking strength cover kg	Length of spool m
3	40	100
4	100	100
5	100	100
6	180	100
7	300	100
8	350	100
10	350	100
12	410	100
14	480	100

Colours



010
Blue
059
Yellow
086
Green
171
Red



228
White
542
White NF
188
Black

Cover

Polyester

Construction

3–8 mm 16-plaited
10–14 mm 24-plaited

Core

premium Latex



LIROS Stretch XTR


00199

High quality Shock Cord with extremely abrasion resistant 100% Dyneema® jacket. Intelligent cover construction design with maximum breakload.

- highest abrasion resistance
- very lightweight
- low water absorption
- UV-resistant

Ø mm	Breaking strength cover daN	Length of spool m
3	150	100
4	290	100
5	300	100
6	320	100

Colour



239
White-Black



Cover

Dyneema®


Construction

16-plaited

Core

high quality Latex rubber

SHOCK CORD



LIROS Quick Clip + Shock Cord

Universal, all-purpose attachment for shock cord. 5 pieces in PE bag.

Reference	Ø mm	Length cm	Reference	Ø mm	Length cm
01905-4050	4	50	01907-8100	7	100
01905-5070	5	70	01907-8140	7	140



LIROS Quick Clip

Useful tightener for shock cords 5 pieces in PE bag or individually available.


01905-0000	single	01905-0001	Five pieces in PE bag
01907-0000	single	01907-0001	Five pieces in PE bag



LIROS Elastic Straps

Our premium braided Polyester shock cord with nylon hook. 5 pieces in PE bag or available individually. High quality stretch latex core for long-lasting elasticity. Perfect for hanging advertising flags or banners. Abrasion and UV-resistant. Made in Germany.

Reference	Ø mm	Length cm	Reference	Ø mm	Length cm
01901-0415	4	15	01901-0455	4	55
01901-0435	4	35	01901-0475	4	75



LIROS Nylon Hook

For 4 mm diameter shock cord. 10 pieces in PE bag.

Reference	Ø mm
01294-0400-228	4



LIROS Nylon-Carabine Hook

Reference	Ø mm
01194-0400-228	4
01196-0600-228	6
01198-0800-228	8

For LIROS Shock Cord Ø 4–8 mm
5 pieces in PE bag.



LIROS Sail Ties

00187-2525-229

Practical sail ties keep your sails safe. Premium end loop stitching for easy tying.

- 5 pieces in LIROS Netbag
- length: 2m



LIROS D-Pro

01505

LIROS Heat-Stretch-System guarantees optimal breaking loads and stretch characteristics of this line. Excellent chafing resistance, light weight, and easy spliceability make this line irreplaceable in all sorts of applications.

- *very strong and abrasion resistant*
- *UV resistant and spliceable*

Reference	Ø mm	Breaking strength kg	Number of spools / length
01505-0002	2	410	10 x 30m
01505-0003	3	950	10 x 15m
01505-0004	4	1300	5 x 10m

Material

pre-stretched, coated Dyneema® SK78

Construction




12-plaited



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Colours



LIROS Magic Speed

01501

Braided Polyester cord point-of-sale box with assorted colours.

- *all-purpose line*
- *round braiding*
- *very robust*

Reference	Ø mm	Breaking strength kg	Number of spools / length
01501-0002	2	95	10 x 30m
01501-0003	3	185	10 x 15m

Material

Polyester



Construction

16-plaited with core

Core

Polyester

Colours





LIROS Magic Sport


01517

Technical high-grade, universally useable line in striking Neon-Design for dinghies and small keel boats. Very abrasion resistant core in cleats, low stretch due to heat-set Polyester core.


- working stretch < 5%
- high visibility colours
- very resistant
- low stretch

Reference	Ø mm	Breaking strength kg	Number of spools / length
01517-0002	2	85	10 x 30m
01517-0003	3	195	10 x 15m

Colours



- 054 Selection
- 417 Neon Yellow-Pink
- 771 Neon Yellow-Silver



- 773 Neon Yellow-Blue
- 781 Neon Yellow-White

Cover

spun dyed Polyester

Construction

16-plaited with core

Core

Polyester



LIROS Braided Polyester Line

01040

Braided high-strength Polyester.

- will not stiffen up
- flexible
- very UV resistant

Reference	Ø mm	Breaking strength kg	Number of spools / length
01040-0002	2	100	10 x 30m
01040-0003	3	200	10 x 15m
01040-0004	4	330	5 x 10m

Material


high-strength Polyester

Construction


8-plaited




Colours



- 054 Selection
- 228 White



- 010 Blue
- 059 Yellow



- 086 Green
- 171 Red
- 188 Black



LIROS Trim Line neon

01522

Popular braided Polyester cord point-of-sale box with assorted colours.

- *all-purpose line*
- *great self-service item*
- *round braiding*



Reference	Ø mm	Breaking strength kg	Number of spools / length
01522-0163-054	3	200	10 x 20m

Material coloured Polyester

Construction 16-plaited with core



LIROS Classic

01172

Design like traditional hemp rope, but softer, stronger and more weather resistant at constant quality.

- *high-grip*
- *pliable*
- *weather resistant*



Ø mm	Number of spools / length
3	10 x 10m

Material spun polyester yarn

Construction 3-strand

Colour



546
Hemp NF



LIROS Optisail

02056

Low-stretch Opti lanyards for longlasting use and great knot holding.

- *working stretch < 1,5%*
- *best knot holding*
- *extremely, strong and pliable*

Ø mm	Number of spools / length
1,2	20 x 20m



BIO-BASED DYNEEMA®

Colour



199
Black-Red

Cover
Polyester

Construction
16-plaited with core

Core
Dyneema® SK78

See our premium metal display rack for best presentation on Point-of-Sale (page 91)



LIROS Whipping Twine / Sewing Thread

Reference	Ø mm	Number of spools / length	Construction	Treatment	Colour
00001	1,0	5 x 30m	plaited	unwaxed	292 White assorted
	1,5	5 x 20m	plaited	unwaxed	292 White assorted
	1,5	5 x 20m	plaited	heavy waxed	292 White assorted
	1,2	5 x 30m	twisted	waxed	292 White assorted
00006	0,5	20 x 80m	twisted	waxed	072 White
00007	1,2	20 x 30m	twisted	waxed	072 White
00008	1,5	20 x 20m	plaited	heavy waxed	072 White
00011	1,0	20 x 30m	plaited	heavy waxed	072 White
00012	1,5	20 x 20m	plaited	unwaxed	054 assorted colours*
00013	1,5	20 x 20m	plaited	heavy waxed	293 assorted colours*
Sewing Thread 00099-0400	0,3	10 x 140m	Polyester		228 White

All whipping twine also available in bulk 500m spools.

*assorted colours: Black, Blue, Green, Red, Yellow

LIROS Dyneema® Waxed Whipping Twine

00016	0,5	20x60m	braided	waxed	529 Silver
00017	1,2	20x30m	braided	waxed	529 Silver



LIROS Whipping twine set

01042-0122

LIROS waxed whipping twine in 1,2mm and a LIROS 00143-4001 micro splicing needle.

- waxed whipping twine white
- micro splicing needle

Ø mm	Length of spool m
1,2	100

Material
Polyester

Construction
twisted



LIROS DC Pro

High-performance, 100% Dyneema® SK99 kiteline. Unmatched ratio between diameter and breaking strength. LIROS DC is perfect for use as flying or bridle line. Extremely low drag values and maximum performance for the kiter. Excellent dimensional stability even after highest stress. Delivers best in kite performance and durable precise control of the sporting equipment.

- easy to splice
- unmatched precision in kite control
- excellent dimensional stability
- LIROS Heat-Stretch-System



Reference	app. Ø mm	Breaking strength kg	Length of spool* m
DC 000-0161	0,83	170	1000
DC 000-0201	1,10	230	1000
DC 000-0301	1,30	325	1000
DC 000-0401	1,55	490	1000
DC 000-0701	2,00	730	1000



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.

Not all colours available in all diameters.

Colours



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Material pre-stretched, coated Dyneema® SK99

Construction 12-plaited

Please find Polyester cover to strengthen splices on page 52.

LIROS DC

High-end, 100% Dyneema® SK75 kiteline. LIROS DC is perfect for use as flying or bridle line. Highest load capacity with minimal line diameter delivers the best in kite performance. Extreme stretch resistance, even after heavy loads, for precise control of the kite. LIROS DC – Kiting without compromise!

- easy to splice
- unmatched precision in kite control
- excellent dimensional stability
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
DC 000-0035**	0,38	35	1000
DC 000-0040	0,50	40	1000
DC 000-0060	0,60	60	1000
DC 000-0100	0,80	100	1000
DC 000-0120	0,85	120	1000
DC 000-0160	1,10	160	1000
DC 000-0200	1,60	200	1000
DC 000-0300	1,80	300	1000
DC 000-0500	2,05	500	1000




* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.

Not all colours available in all diameters.

** DC 000-0035 only available in 228 White and 659 Orange.

Colours



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Material pre-stretched, coated Dyneema® SK75

Construction 12- and 16-plaited

Please find Polyester cover to strengthen splices on page 52.




LIROS PC

Very long-lived and abrasion resistant cover for LIROS flying lines. A flexible braid made of high quality polyester protects the flying line and guarantees best connection properties.

- long-lived
- UV-resistant
- cover material without core

Colours



Material hollow-braided Polyester

Reference	suitable for	Length of spool* m
PC000-0060	DC60, DC100	100
PC000-0120	DC120, DC160, DC161, DC201	100
PC000-0200	DC200, DC301	100
PC000-0300	DC300, DC401, DC701	100



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.

LIROS Bridle Line

LIROS Bridle Line is the reliable and durable bridle line with minimal stretch characteristics. The very abrasion-resistant and compact braided Polyester cover makes this rope glide perfectly through pulleys and has direct influence on kite control.

- low elongation
- high abrasion resistance
- compact
- safe

Colour



Reference	app. Ø mm	Breaking strength kg	Length of spool* m
22138-0200	2,0	300	1000
22138-0330	3,3	500	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.



Cover high-strength Polyester **Construction** 12-plaited **Core** Dyneema® plaited



LIROS DePower Lines

Specially designed Depower line made of 100% Dyneema®. For long-life cycle in modern kitebar constructions. Technically versed coatings deliver up to 30% more resistance against abrasion, than in common depower lines.


- highest safety and perfect abrasion resistance for the kiter
- spliceable
- very good abrasion resistance
- high breaking load
- low elongation
- LIROS Heat Stretch System

Reference	app. Ø mm	Breaking strength kg	Length of spool m
DPLPO-1300	4,0	1300	100/500
DPLPO-1750	4,5	1750	100/500
DPLPO-2600	5,0	2600	100/500
DPL00-1550	4,4	1550	500
DPL00-1700	5,2	1700	500
DPL00-1800	5,6	1800	500



LIROS HSS
Heat Stretch System
LIROS LCS
LIROS Coating System

Colours



716
Silver
521
White



735
Deep Black

Material Dyneema®

Construction plaited, heat set and coated

LIROS PPSLS

Thin + Safe + Longlasting. Unique breakload at thinnest diameter guarantees highest performance for the paraglider. Minimum elongation for ideal glider setup. The paragliding line for high demands.

- extremely light and thin
- highest breakloads
- best paragliding performance
- perfect aging properties
- LIROS Heat-Stretch-System


Reference	app. Ø mm	Breaking strength kg	Length of spool* m
PPSLS-0065	0,76	65	1000
PPSLS-0125	1,05	130	1000
PPSLS-0160	1,15	160	1000
PPSLS-0180	1,25	180	1000
PPSLS-0200	1,3	200	1000
PPSLS-0260	1,58	260	1000




* LIROS FlightSport lines may come six pieces to a spool. No line will be shorter than 25m.

Not all colours available in all diameters.

Colours



010
Blue
059
Yellow
086
Green



150
Orange
171
Red



LIROS HSS
Heat Stretch System

Cover Polyester

Core pre-stretched Dyneema®



LIROS PPSL

LIROS PPSL is lightweight, with minimal creep, as well as unmatched durability, even after extreme bending. The kite line for the most demanding applications. Shrinkage < 0,5%.






- very low creep
- lowest stretch
- top paragliding performance
- optimal dimensional stability
- extremely durable
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
PPSLO-0120	1,15	120	1000
PPSLO-0160	1,40	160	1000
PPSLO-0191	1,20	190	1000
PPSLO-0200	1,42	200	1000
PPSLO-0275	1,90	275	1000
PPSLO-0350	2,25	350	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25 m.
Not all colours available in all diameters.

Colours

 010 Blue	 086 Green	 171 Red
 059 Yellow	 150 Orange	

Cover Polyester 16-plaited
Core pre-stretched Dyneema®



LIROS HSS
HeatStretchSystem

LIROS DSL

High-tech Dyneema® core, combined with our superior Polyester braided cover, guarantees a long-lasting, high-altitude line. Perfectly balanced Polyester cover offers the best in line accessibility and protects the core from dirt and UV exposure.







- very low creep
- lowest stretch
- good line differentiation
- optimum durability
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
DSL00-0025 Black	0,80	25	1000
DSL00-0035 White	0,90	35	1000
DSL00-0070	0,95	70	1000
DSL00-0140	1,25	140	1000
DSL00-0350	2,00	350	1000
DSL00-0600	2,40	600	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25 m.
Not all colours available in all diameters.

Colours

 010 Blue	 086 Green	 157 Pink
 059 Yellow	 150 Orange	 171 Red

Cover Polyester 32-plaited
Core pre-stretched Dyneema®



LIROS HSS
HeatStretchSystem



LIROS TSL

LIROS TSL is the covered Technora® paragliding line with the best diameter to load capacity ratio. Optimised cross-section for excellent aerodynamics. High-strength Technora® fibres and LIROS Heat-Stretch-System to minimise stretch and creep. Finely braided, water-repellent Polyester cover provides easy line differentiation.


- optimal diameter to load capacity ratio
- lowest creep, lowest stretch
- optimum bendability
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
TSL00-0115	1,25	115	1000
TSL00-0140	1,30	140	1000
TSL00-0190	1,55	190	1000
TSL00-0220	1,65	220	1000
TSL00-0280	1,80	280	1000
TSL00-0380	2,20	380	1000
TSL00-0500	2,37	500	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.
Not all colours available in all diameters.

Colours



010
Blue



086
Green



171
Red



059
Yellow



150
Orange

Cover Polyester

Core Technora®

Technora®

The power of Aramid

LIROS HSS

Heat Stretch System

LIROS LTC

LIROS LTC - performance at its best! The high tech line with double coating for the best in aerodynamics. The unique LIROS LTC process coats Technora® fibres before braiding for the best in static hold, UV stability, lateral strength, and line handling. LIROS LTC is the perfect line for competitive and advanced-intermediate use.

- lowest stretch
- very low creep
- double nanocoating
- optimum surface finish
- peak performance
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
LTC00-0045	0,55	45	1000
LTC00-0065	0,65	65	1000
LTC00-0080	0,70	80	1000
LTC00-0120	1,10	120	1000
LTC00-0160	1,20	160	1000
LTC00-0200	1,30	200	1000
LTC00-0350	1,75	350	500
LTC00-0400	1,90	400	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.

Colour



705
Beige NF

Technora®

The power of Aramid

LIROS HSS

Heat Stretch System

LIROS LCS

LIROS Coating System

Material 100% Technora®

Construction 12-plaited



LIROS DFL

LIROS DFL offers a high degree of flexibility. Very good knot holding and UV resistance, excellent for brake lines. LIROS DFL handles high dynamic load ranges easily, especially in deflection through turning blocks.

- good knot hold
- extremely abrasion resistant
- lightweight
- highly flexible

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
DFL00-0115	1,40	115	1000
DFLS0-0200	1,90	200	500
DFLPO-0232	2,70	200	500
DFL00-0350	2,70	350	500



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.

DFLS0 only available in 059 Yellow and 150 Orange.

Colours



059 Yellow



150 Orange



171 Red

Cover Polyester 16-plaited, DFLPO-0232 32-plaited
Core Dyneema®



LIROS Safety Line

LIROS Safety Line was specially engineered for safety equipment applications, and is optimised for stretch and shock loading compensation. Developed to deliver the ultimate in safety.

RLP

- working stretch < 25%
- excellent damping capabilities
- good spliceability
- Material: Polyamide

RLD

- working stretch < 7%
- good spliceability
- high weight reduction
- Material: Dyneema®


Reference	app. Ø mm	Breaking strength kg	Length of spool* m
RLD00-0190	1,3	190	500
RLD00-0275	1,35	275	1000
RLD00-0350	1,7	350	1000
RLP00-0110	4	110	1000
RLP00-0150	4,5	150	1000



* LIROS Flightsport lines may come six pieces to a spool. No line will be shorter than 25m.



Colour



228 White




LIROS SL

Very long lasting and lightweight towing line for paragliding and winch towing. LIROS SL delivers a high level of safety. The SL500 is especially well-suited for tandem towing. The extremely thin diameter increases capacity on winch drums.

- easy to splice
- low diameter increases winch capacity
- no water absorption
- very good UV resistance

Reference	app. Ø mm	Breaking strength kg	Length of spool m
SL000-0375	2,5	375	1000
SL000-0500	3,2	500	1000

Colour



228
White



Material Dyneema® **Construction** SL375 12-plaited / SL500 8-plaited

LIROS Harness

Extremely flat hollow braided rope. LIROS Harness is qualified to replace common webbings in paragliding harness. Made of 100% Dyneema® for less weight and very good flexibility endurance and resistant to fatigue.

- lightweight
- high breakloads
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool m
CRS00-0500-228	5	500	500
CRO00-1000-228	6	1000	500
CRO00-1800-228	9	1800	500

Colour



228
White



Material 100% Dyneema® **Construction** 32-plaited


LIROS T-Webbing

00185-1301

Technora® webbing with Polyester cover. A LIROS development for use in paragliding ultra light harnesses. Longlasting high tech quality.

- high breakloads
- good resistance to abrasion

Colour



188
Black

Material Technora®/Polyester **Construction** webbing

app. width mm	Breaking strength kg	Length of spool m
13	850	100

Technora®
The power of Aramid



LIROS V-Plus-XTR 04007


V-Plus-XTR is made of 100% Vectran® with high tech XTR Coating. Perfect as a wire replacement or alternative to hard shackles. An ideal line for applications that require constant length, lowest stretch without creep, also under load. Vectran® delivers extreme precision. Perfect as bolt rope for high performance sails.

- grip factor 7
- no creep
- XTReme low initial elongation
- high-tech XTR coating
- easy to splice
- heat resistant



Ø mm	Weight g/m	Working stretch %	Breaking strength kg
2	3	< 1,0	400
3	7	< 1,0	1100
4	10	< 1,0	1500
5	22	< 1,0	3000
6	32	< 1,0	5000
8	48	< 1,0	6800

Material 100% Vectran® with LCS Coating
Construction 12-plaited



LIROS D-Pro 01505

LIROS Heat-Stretch-System for guaranteed optimum breaking load and lowest stretch. Top abrasion resistance, low weight, and easy spliceability make this line irreplaceable in numerous show-rigging applications. Perfect as a replacement for steel cables.

- mat black surface, not marking off
- non-reflective
- working stretch < 1 %
- very high working load with minimum diameter and lightweight
- first choice for all extreme load applications
- best spliceability
- high UV stability and abrasion resistance
- LIROS Heat-Stretch-System




Material Dyneema® SK78 coated
Construction pre-stretched, coated, 12-plaited

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
2	410	1,8	100
2,5	580	3,5	100
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
9	7500	49	100
10	9000	60	100
12	11900	72	100
14	14500	95	100
16	19000	131	100



Not certified for lifting loads and personal security!



LIROS Max Load Black 02025

Full spectrum black cover is completely invisible in dark environments. High-quality, very low-stretch, with durable and abrasion resistant braided cover, inner cover and special coated Dyneema® SK78 core.

- working stretch < 1,5%
- exceptionally strong, durable, and lightweight
- extremely abrasion resistant Polyester cover
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
2	270	3	250
2,5	390	5	250
3	550	7	250
4	800	11	250
5	1100	15	250
6	2500	25	200
8	3800	42	200
10	5000	61	200
12	7200	88	200

Colour



525
Black NF



LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Cover

special high-twisted Polyester

Construction

2-3 mm 16-plaited
4 mm and up 1:1 plaited

Core

coated Dyneema® SK78 with additional cover plait from 8 mm and up



LIROS Poly Black 01076

Affordable, extremely lightweight rope for theatre and other applications. Very easy-to-handle, deep black soft Polypropylene.

- working stretch < 12%
- very lightweight
- easy to handle
- floatable
- UV stabilised
- economical



Colour



525
Black NF

Ø mm	Breaking strength kg	Length of spool m
1,5	38	100
2	70	100
3	140	100
4	280	100
5	390	250
6	550	200
8	900	200
10	1230	200
12	1700	200
14	2000	150
16	3700	100

Material

Polypropylene multifilament

Construction

8-plaited



LIROS Multi Black

01037

High-strength black braided Polyester. High-grip surface. Multi-purpose line.

- working stretch < 10%
- will not stiffen up
- very UV resistant
- flexible
- abrasion resistant



Colour



525
Black NF

Material

high-tenacity Polyester

Construction

16-plaited with core up to 8mm
20-plaited with core 10mm and up

Core

high-tenacity Polyester

Ø mm	Breaking strength kg	Length of spool m
1	35	100
2	90	100
3	150	100
4	280	100
5	450	250
6	640	200
8	1100	200
10	1700	200
12	2200	200
14	3000	150
16	3900	100

LIROS Soft Black

00174

Premium quality, high-grip Polyester line with flexible, soft-grip cover. Matt black cover is completely invisible in dark environments.

- working stretch < 6%
- soft easy-to-handle premium spun braid
- excellent knot hold



Colour



525
Black NF

Cover

Polyester

Construction

Ø 5 mm 8-plaited
Ø 6 to 8 mm 16-plaited
Ø 10 to 12 mm 20-plaited
Ø 14 mm and up 24-plaited

Core

high-tenacity Polyester

Ø mm	Breaking strength kg	Length of spool m
5	300	250
6	520	200
8	1000	200
10	1900	200
12	2400	200
14	2900	150
16	3400	100



LIROS Safe Nordic Plus

01019-0000

Core-cover rope, manufactured to **DIN EN 1891** for personal security. Specially designed with extremely low stretch for SRT (Stationary Rope Technique), or as efficient and power saving abseiling rope. Robust and resistant, very good grip and smooth handling. With optimized cover structure for optimal fulfilling the requirements of single-rope technique.

- *very low stretch*
- *grippy and flexible*
- *robust and resistant*
- *available pre-spliced with sewn eye on both ends*

Cover
high-tenacity Polyamide

Construction
16-1:1 plaited

Core
high-tenacity Polyamide



Ø mm	Breaking strength kg	Elongation % at 100kg	Weight g/m	Cover ratio %	Length m
9,6	2900	3,8	62	60	as required

Colour



790
White 2F Black



LIROS Safe Nordic

01015-0000

Semi-static rope manufactured to **DIN EN 1891** standards. Developed by LIROS for specialised industrial applications with double-braided construction and LIROS Heat-Stretch-System for minimal core-cover movement.

- *low yo-yo effect when up- and abseiling*
- *very good handling*
- *non-kinking and easy stowing*
- *available with both ends sewn eye*

Cover
high-tenacity Polyamide

Construction
32-plaited

Core
high-tenacity Polyamide



Ø mm	Breaking strength kg	Elongation % at 100kg	Weight g/m	Cover ratio %	Length m
11,5	3400	3,8	80	46	as required

Colour



701
Black 2F Red





LIROS Safe Classic

The LIROS semi-static rope is a strong and durable rope for life safety/rescue applications, or rope access/scaffolding. The unique abrasion-resistant braided cover protects the core from external weather conditions and dirt. Manufactured according **DIN EN 1891**.

- long-lasting construction
- highly abrasion resistant
- exceptional knot hold
- extremely low cover-core movement
- available with both ends sewn eye

Cover
high-tenacity Polyamide

Construction
16-plaited

Core
special multi-braided Polyamide



Reference	Ø mm	Breaking strength kg	Elongation % at 100 kg	Weight g/m	Cover ratio %	Length m
00099-1116	10,5	3400	4,1	70	42	as required
00099-2369	11	3550	4,0	74	40	as required

Colours



382
White-Blue-Black



525
Black NF



LIROS Safe Pro

01011

Semi-static rope manufactured to **DIN EN 1891** standards. Developed by LIROS for specialised industrial applications with double-braided construction and LIROS Heat-Stretch System for minimal core-cover movement.

- available with both ends sewn eye
- soft and flexible rope
- perfect and easy handling
- LIROS Heat-Stretch-System

Cover
high-tenacity Polyamide

Construction
32-plaited

Core
high-tenacity Polyamide




Reference	Ø mm	Breaking strength kg	Elongation % at 100 kg	Weight g/m	Cover ratio %	Length m
01011-1000	10	2600	4,4	58	43	as required
01011-1100	11	2850	4,2	71	53	as required
01011-1200	12	3900	4,0	82	45	as required
01011-1400	14	4550	3,4	102	46	as required

Colour



230
White-Blue-Yellow





LIROS Safe Vision

01595 / 01596



New LIROS safety rope according to **DIN EN 1891**. Specially developed as a working line for the arborist. LIROS Safe Vision is especially smooth and flexible, so arborists can work and move quickly and safely. High strength Polyester cover is extremely abrasion resistant. Low diameter for very lightweight.

- optimum handling
- highly abrasion resistant
- exceptional knot hold
- extremely low cover-core movement

Cover
high twisted Polyester

Construction
24-plaited

Core
plaited Polyamide



Colour



014
Blue-Yellow-White

Reference	Ø mm	Elongation % at 100 kg	Breaking strength DIN kg	Breaking strength eff. kg	Weight g/m	Cover ratio %	Length m
01595-0000	11,8	2,5	2200	3700	82	54	as required / without end connection
01595-1000	11,8	2,5	1500	2900	82	54	as required / incl. seam
01595-3000	11,8	2,5	1500	2400	82	54	as required / incl. splice
01596-0000	12,8	2,2	2200	4500	102	51	as required / without end connection
01596-1000	12,8	2,2	1500	3300	102	51	as required / incl. seam
01596-3000	12,8	2,2	1500	3000	102	51	as required / incl. splice



LIROS Safe Plus

01597-0000



The LIROS Safe Plus is a specially designed double braid manufactured and certified to **DIN EN 1891** Type A. Developed for „Single Rope Technique“ (SRT). Perfect control for efficient ascending, abseiling and working technique. The special construction with comparable reduced elongation with best breaking strength avoids any yo-yo effect during the ascent. This allows the pro-arborist to concentrate fully on his work and the safety improves considerably.

- available with both ends sewn eye
- exceptional knot hold

Cover
Polyester

Construction
32-plaited

Core
Polyamide



Colour



652
Neon Yellow-Black

Ø mm	Breaking strength kg	Elongation % at 100 kg	Weight g/m	Cover ratio %	Length m
11,5	4300	1,5	100	46	as required



LIROS Safe Prusik XTR 01594

LIROS Prusik-XTR, according to **DIN EN 566**, is notable for its high strength and technical construction, with a special combo-material cover of heat-resistant hybrid fibres paired with high-strength Polyester.

- *very high strength*
- *impact force: 5.5 kN*
- *excellent abrasion resistance, even at high temperatures*
- *perfect cover-core attachment*
- *multiple applications*
- *sewn eye on each end*
- *standard length 60, 70, 80, 90, 100, 110 and 120cm*

Ø mm	Breaking strength DIN kg	Breaking strength eff. kg
9	2200	2900

Cover
Aramid / Polyester
24-plaited


Core
Dyneema®, Aramid



Colour



192
Black-Yellow



LIROS Safe Prusik 01590 / 92 / 93

LIROS Prusik, according to **DIN EN 566**, is notable for its technical construction, with a special combo-material cover of heat-resistant hybrid fibres paired with high-strength Polyester.

- *excellent abrasion resistance, even at high temperatures*
- *hybrid fibres inhibit cover melting*
- *perfect cover-core attachment*
- *multiple applications*
- *sewn eye on each end*
- *standard length 60, 70, 80, 90, 100, 110 and 120cm*

Reference	Ø mm	Breaking strength DIN kg	Breaking strength eff. kg
01592	8	2200	2500
01590	9,1	2200	2700
01593	10	2200	2900

Cover
Polyester / Aramid 20-plaited

Core
high-tenacity Polyester



Colour 01590



064
Yellow-Red

Colour 01592



321
Yellow-Silver

Colour 01593



069
Yellow-Green



LIROS Safe Arb

01527

Very easy-to-handle rope, extremely strong and durable. 100% Polyester cover-core construction will not stiffen up. Specially developed LIROS Coating for exceptional abrasion resistance.

- very easy to splice
- extremely strong and durable
- will not stiffen up
- very UV-resistant



LIROS LCS
LIROS Coating System

Ø mm	Breaking strength kg	Length of spool m
12	4500	as required
14	5500	as required
16	6700	as required
18	7600	as required

Colours



12 mm
010 Blue



14 mm
059 Yellow



16 mm
171 Red



18 mm
188 Black

Cover
high-twisted Polyester

Construction
20-plaited

Core
high-tenacity braided Polyester

LIROS Heaving Line

01519-0180

Designed through technical innovation and longevity in mind. Forms loose coils and guarantees easy throwing. High visibility to ensure safe working practice.

- kink resistant
- abrasion resistant
- spliceable

Colours



059
Yellow



096
Light Blue

app. Ø mm	Breaking strength kg	Length of spool m
1,8	200	100



LIROS HSS
Heat Stretch System
LIROS LCS
LIROS Coating System

Material Dyneema® impregnated
Construction braided



LIROS Safe Spill

01525

Capstan Winch Rope with high-strength core and abrasion resistant Polyester cover. The special core material provides an extremely high breaking strength and safety at lowest weight. Customised lengths available.

- working stretch < 1%
- abrasion and heat resistant
- very good knot hold
- very UV-resistant

Colour



239
White-Black

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
10	3800	70	200

Cover high-strength Polyester

Construction 1:1 plaited

Core HMPE




LIROS D-Steel

01481

With this line LIROS guarantees highest breaking strength and lowest elongation values with all diameters, best abrasion resistance, low weight and easy spliceability. Enabling new and innovative solutions in forestry and arboriculture. Optimal as replacement of steel ropes in various technical applications.

- working stretch < 1%
- very high breaking load with smallest diameter and lowest weight
- first choice for all applications with extreme loads
- 10 x lighter than steel
- excellent spliceability, can also be used with cover
- high UV stability and durability
- water repellent
- LIROS Heat-Stretch-System

Colour



316
Carbon



Ø mm	Breaking strength kg	Length of spool m
8	6800	100/as required
10	10500	100/as required
12	14500	100/as required
14	17500	100/as required
16	22000	100/as required
18	26000	100/as required
20	32000	100/as required
22	38000	100/as required
24	44000	100/as required
26	50000	200 (coil)

Material ultrahigh-strength HMPE
Construction 12-plaited, heat set and coated

LIROS Felling Aid Rope

02008

Our very low weight and abrasion resistant PES-Vectran Fällhilfeseile / tree towing rope is manufactured with extremely low stretch HMPE-core. The indicated Forest Tractive Force (FTF) on the respective Fällhilfeseil resembles the maximum traction of your forestry windlass.

- working stretch < 1%
- with FTF-label 2,5t, 4,5t, 6t, 8,5t or 10t
- available length: 9, 12, 15, 20, 30 and 40m
- extremely abrasion resistant PES-Vectran protective cover
- eye splice on both ends (length 200mm)
- long service life
- extremely low weight at high breaking strength

Cover

50% Vectran® / 50% Polyester
32-plaited

Construction

32-plaited

Core

Dyneema® SK78 with XTR-Grip-Coating Silver



Vectran™



Ø mm	Breaking strength kg	FTF t	Weight g/m
10	6900	2,5	40
12	9900	3,5	80
14	13000	4,5	120
16	15200	6,5	160
18	18500	7,5	200
20	21700	8,5	240
22	24600	10	280



Colours



263
Beige-Steelblue
419
Beige-Orange



LIROS Offroad XTR

04010

The world first LIROS XTR Offroad!

100 % Vectran® winch rope special braid with utility patent protected end connection without metal parts. The easy-to-use LIROS Soft Shackle ensures a permanently secure connection.

- Flexible and lightweight with extreme breaking load
- Permanently integrated high-strength LIROS Soft Shackle
- Constructed from high-tech material Vectran® extremely heat resistant
- Low noise and easy handling
- Minimize the risk of injury due to use of 100% textile fibers
- No metal components to prevent scratching the paint
- Signal colour „red“ for safe and fast work in the field and in poor visibility
- Registered design (DPMA)

LIROS Offroad Extension

04010-0901

This rope is the extension for the Liros Offroad XTR. It can be used with every conventional winch rope. The length is infinitely variable and can be shorted to approximately half the length. Using this material is far superior in terms of handling and safety.

- Flexible and lightweight with extreme breaking load
- Length easily changeable
- Constructed from high-tech material Vectran® extremely heat resistant
- Signal colour „red“ for safe and fast work in the field and in poor visibility
- Low noise
- Safer and easier to handle
- Minimize the risk of injury due to use of 100% textile fibers

Ø mm	Breaking strength kg	Weight kg / pce.	Length m
9,4	9000	2,4	27
11	10800	2,7	20

Material 100% Vectran® with XTR-Coating

Construction 12-plaited

Colour



638
Red

Vectran™

LIROS LCS
LIROS LCS Coating System

Ø mm	Breaking strength kg	Weight kg / pce.	Length m
9,4	9000	0,76	10

Material 100% Vectran® with XTR-Coating

Construction 12-plaited

Colour



638
Red

Vectran™

LIROS LCS
LIROS LCS Coating System

NEW



OFFROAD




LIROS Offroad Winch Rope

Specially-designed recovery rope for extreme winch applications. Perfect replacement for wire cable. Strong and 10x lighter than steel, LIROS Offroad Winch Rope offers perfect performance and safety. Ready-to-use: carabine hook on one end, plus 2 movable protective jackets for friction points. Winchend: special flat terminal for winch drum attachment, protected by 3m heat resistant monofilament braid.

- working stretch < 1 %
- extremely high breaking load with smallest diameter and lowest weight
- Two 1 m protective jackets
- ideal replacement for steel cable
- very easy to splice
- high UV stability and abrasion resistance
- LIROS Heat-Stretch-System

Colour



316
Carbon

LIROS HSS
Heat Stretch System
LIROS LCS
LIROS Coating System

Material ultra high-strength HMPE

Reference	Ø mm	Length m	Winch size t	Breaking strength rope kg
01481-0602	6	20	1,3	4000
01481-0603	6	30	1,3	4000
01481-0801	8	30	4,3	5500
01481-0802	8	40	4,3	5500
01481-1001	10	30	4,3	8500
01481-1002	10	40	4,3	8500

Hook breaking strength: 2.5t safe working load



* Winner in "4X4 Action" Magazine for real offroaders. 6 other winch lines tested (4/2014 issue)

LIROS Offroad Towing Rope

LIROS Offroad Towing Rope has been specially designed by LIROS to withstand extremely high forces during dynamic towing (e.g. in sand). The line make it possible to drag stranded SUVs out of the toughest situations. Both ends eye with protective sleeve of abrasion resistant Polyester

- double-ended eyes with protective sleeve
- up to 30% stretch under shock loading
- extremely easy to handle under working conditions
- custom lengths available



Material high-tenacity Polyamide


Construction

8-strait octoplait

Colours



188
Black



228
White

Reference	Ø mm	Breaking strength kg	Length of spool m
01058-2401	24	9500	5
01058-2402	24	9500	8
01058-2403	24	9500	12
01058-2404	24	9500	15
01058-2802	28	12000	9
01058-2803	28	12000	12
01058-2804	28	12000	15


LIROS Offroad Performance

**01481
-1201**

LIROS XTR Towing has been developed in collaboration with the best teams in international desert rallying. Successfully tested with the most prestigious teams. LIROS XTR Towing is 100% textile high-strength material. It replaces heavy wire ropes and steel fittings. The two integrated LIROS Soft Shackle enable a fast and secure connection. Best handling thanks to low weight.

- Flexible and lightweight with maximum breaking load
- Two integrated high-strength LIROS Soft Shackles
- Registered design (DPMA)
- Low noise and easy handling
- Minimize the risk of injury due to use of 100% textile fibers
- No metal components to avoid scratching the paint

Colour



316
Carbon-Red

Material

100% HMPE with XTR-Coating

Confection

Both ends LIROS Special Soft Shackle

LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Ø mm	Breaking strength kg	Weight kg/pce.	Length of spool m
12	13000	1,3	12




OFFROAD

LIROS Offroad Shackle

LIROS Offroad Shackle combines exceptional flexibility and super light weight with enormous breaking load. Extremely abrasion resistant protective sleeve specially developed for off-road use gives this shackle tremendous durability and massive holding power. A must for offroaders.

- super lightweight and easy to handle
- high breaking load
- can't open accidentally under load
- reduces risk of injury
- premium LIROS quality

Colour



316
Carbon



Material


100% Dyneema®

LIROS HSS
Heat Stretch System

LIROS LCS
LIROS Coating System

Protective sleeve

Polyester



Reference	Breaking strength kg	SWL** kg	A material Ø mm	B final Ø app. mm	C inner length mm
00146-0077	7000	4000	10	18,5	220
00146-0078	12000	7000	12	21	240
00146-0079	20000	12000	14	23	270
00146-0317	35000	21000	16	42	300

** SWL = Safe Work Load




Not certified for lifting loads and personal security!



Unlimited Rope Solutions for steel rope replacement

LIROS high tech fiber ropes are perfect for replacing steel ropes and offer many advantages! Exceptional strength to weight ratio, ultimately leads to a cost saving through innovative design and less component requirements.

- LIROS O1505 D-Pro
- LIROS O1418 D-Steel
- LIROS O2000 Regatta 2000
- LIROS OO146 Soft Shackle
- LIROS OO148 Dyneema® Braid
- LIROS EO148 Dyneema® Braid



More than
3x

Longer lifespan than HMPE due to reduced material fatigue

up to
4x

More resistance to creep than other HMPE fibers

Best performance between

-40°C to 70°C



LIROS D-Steel


01481

With this line LIROS guarantees highest breaking strength and lowest elongation values with all diameters, best abrasion resistance, low weight and easy spliceability. Enabling new and innovative solutions in forestry and arboriculture. Optimal as replacement of steel ropes in various technical applications.

- working stretch < 1 %
- very high breaking load with smallest diameter and lowest weight
- first choice for all applications with extreme loads
- 10x lighter than steel
- excellent spliceability, can also be used with cover
- high UV stability and durability
- water repellent
- LIROS Heat-Stretch-System

Ø mm	Breaking strength kg	Length of spool m
8	6800	100/as required
10	10500	100/as required
12	14500	100/as required
14	17500	100/as required
16	22000	100/as required
18	26000	100/as required
20	32000	100/as required
22	38000	100/as required
24	44000	100/as required
26-40	50000	as required

Colour



316
Carbon



Material

ultra high-strength HMPE

Construction

12-plaited, heat set and coated

LIROS Dyneema® Braid

LIROS offers a comprehensive range of braided Dyneema® lines which can be used in industry as well as the nautical and aviation environments.

- working stretch < 1 %
- extremely strong
- very low stretch
- available in diameters from 0,06–24 mm
- custom lengths, construction, and colour impregnation available
- 500m X-Spool standard

Reference	Ø mm	Breaking strength kg	Construction
00148-0006	0,06	3,8	3-plaited
00148-0014	0,14	8,0	3-plaited
00148-0018	0,18	11,5	3-plaited
00148-0024	0,24	16	6-plaited
00148-0030	0,3	25	6-plaited
E0148-0049	0,49	46	12-plaited
E0148-0058	0,58	80	16-plaited
E0148-0079	0,79	104	12-plaited
E0148-0085	0,85	130	16-plaited
E0148-0110	1,10	170	12-plaited
E0148-0111	1,11	200	12-plaited
E0148-0151	1,5	300	12-plaited
E0148-0161	1,6	400	12-plaited
E0148-0201	2,0	700	12-plaited

Material

Dyneema®



Colour



228
White

Additional diameters available upon request.




LIROS D-Pro

01505

LIROS Heat-Stretch-System guarantees optimal breaking loads and stretch characteristics of this line. Excellent chafing resistance, light weight, and easy spliceability make this line irreplaceable in all sorts of applications on racing boats of any size. Perfect as a replacement for steel cabling in technical applications.








- working stretch < 1 %
- very high breaking load with small diameter and very low weight
- first choice for any application under extreme loads
- very spliceable
- highly UV stable and chafe resistant
- LIROS Heat-Stretch-System

Material Coated Dyneema® SK78
Construction 12-plaited, heat-set and coated

 *Not certified for lifting loads and personal security!*

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
1	195	0,9	100
1,5	230	1,3	100
2	410	1,8	100
2,5	580	3,5	100
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
9	7500	49	100
10	9000	60	100
12	11900	72	100
14	14500	95	100
16	19200	131	100

Colours

	010 Blue		171 Red		228 White
	059 Yellow		205 Silver		674 Deep Black (2 and up)
	086 Green				



LIROS Aramid

00144

Very low stretch, durable and strong Aramid rope with Polyester cover for optimal UV and abrasion resistance.

- working stretch < 1,5 %
- strong
- extremely low stretch



Cover Polyester
Construction up to 2.5 mm 16-plaited
 3.5 mm and up 1:1 plaited
Core braided Aramid

Ø mm	Breaking strength kg	Length of spool m
2	170	500
2,5	260	500
3,5	500	500
5	800	250
6	1100	200
8	2000	200
10	2600	200
12	3600	200
14	5200	150

Colours

	236 White-Red		525 Black NF
---	------------------	---	-----------------



LIROS LTC

LIROS LTC - performance at its best! The high tech line with double coating for the best in aerodynamics. The unique LIROS LTC process coats Technora® fibres before braiding for the best in static hold, UV stability, lateral strength, and line handling. LIROS LTC is the perfect line for competitive and advanced-intermediate use.


- lowest stretch
- very low creep
- double nanocoating
- optimum surface finish
- peak performance
- LIROS Heat-Stretch-System

Reference	app. Ø mm	Breaking strength kg	Length of spool* m
LTC00-0045	0,55	45	1000
LTC00-0065	0,65	65	1000
LTC00-0080	0,70	80	1000
LTC00-0120	1,10	120	1000
LTC00-0160	1,20	160	1000
LTC00-0200	1,30	200	1000
LTC00-0350	1,75	350	500
LTC00-0400	1,90	400	500



* LIROS LTC lines may come in pieces to a spool. No line will be shorter than 25 m.

Colour



705
Beige NF

Technora®
The power of Aramid

LIROS HSS
Heat Stretch System
LIROS LCS
LIROS Coating System

LIROS Aramid Cord 00147

Extremely strong and low-stretch cord for specialised industrial and leisure applications. Extremely strong, low stretch, with high heat resistance.

- working stretch < 1,5%
- very good steel cable replacement
- customised lengths available
- additional diameters available upon request

Ø mm	Breaking strength kg	Construction	Length of spool m
0,4	45	6-plaited	500
0,9	80	6-plaited	500
1	100	16-plaited	500
1,5	135	8-plaited	500
2,1	290	8-plaited	500
3	560	12-plaited	500
4	700	12-plaited	500
5	1000	12-plaited	250
6	2000	12-plaited	200

Colour



059
Yellow

Material
braided Aramid

Twaron®
The power of Aramid



8-plaited

16-plaited

LIROS Polyester Braid 01037 / 01038 / 01040

High-strength Polyester rope. Flexible, very UV- and abrasion resistant. Will not stiffen up.

- working stretch < 10%
- custom lengths available



Colour 01037



525
Black

Colour 01038



228
White

Colours 01040



010
Blue



059
Yellow



086
Green



171
Red



188
Black



228
White

Material
high-tenacity Polyester

Construction 01037 / 01038

up to 8 mm 16-plaited with core
10 mm and up 20-plaited with core

Construction 01040

1 mm - 1,5 mm
6-plaited
2 mm and up
8-plaited

	Ø mm	Breaking strength kg	Length of spool m
White & Colour	1	45	500
	1,5	65	500
	2	100	500
	2,5	150	500
	3	200	500
	4	330	500
	5	500	250
	6	800	200
	8	1150	200
White & Black	10	2000	200
	12	2900	200
	14	3900	150
	16	4200	100


LIROS Polyester Spiral Braid 01045

Flexible high-strength Polyester rope. Very UV- and abrasion resistant and will not stiffen up.

- working stretch < 10%
- custom lengths available



Colour



228
White

Material
high-tenacity Polyester

Construction
spiral-plait

Ø mm	Breaking strength kg	Length of spool m
3	160	500
4	280	500
5	435	250
6	670	200
8	840	200
10	1500	200
12	2200	200
14	3600	150



8-plaited

LIROS Polyamide Braid 01025 / 01030 / 01027

High strength Polyamide Cord. Highly elastic and flexible, very UV- and abrasion resistant.

- *working stretch < 15%*
- *custom lengths available*

Material

high-tenacity Polyamide


Construction 01025 / 01030

0,5 mm - 1 mm
6-plaited
1,5 mm and up
8-plaited

Construction 01027

16-plaited with core

Colour 01025



228 White

Colour 01027



228 White


Colours 01030



010 Blue



059 Yellow



086 Green



171 Red



188 Black



16-plaited

	Ø mm	Breaking strength kg	Length of spool m
01025/01030			
White	0,5	15	500
White & Colour	1	50	500
	1,5	65	500
	2	115	500
	2,5	160	500
	3	200	500
	3,5	300	500
	4	350	500
	5	570	250
	6	880	200
	8	1600	200
	10	2400	200
White & Black	12	3200	200
	14	3600	150
	16	4300	100
01027			
White	1,5	50	500
	2	110	500
	2,5	190	500
	3	240	500
	4	400	500
	5	590	250
	6	1000	200
	8	1800	200
	10	2800	200



LIROS Polyamide Spiral Braid 01035

Spiral plaited Polyamide Cord. Round, flexible, high stretch and very UV-resistant.

- *working stretch < 20%*
- *custom lengths available*

Colour 01035



228 White



Material

high-tenacity Polyamide

Construction

spiral braiding

Reference	Ø mm	Breaking strength kg	Length of spool m
01035	2	90	500
	2,5	120	500
	3	160	500
	3,5	210	500
	4	290	500
	5	450	250
	6	600	200
	8	1000	200
	10	1800	200
	12	2200	200
	14	2800	150
	16	3600	100



LIROS Coloured Polypropylene Braid

01072

Spun-dyed Polypropylene multifilament. Economical with wide variety of use.

- working stretch < 12%
- UV stabilised
- 6 mm and up with blue/gold flecks
- custom lengths available

Ø mm	Breaking strength kg	Length of spool m
1	30	500
1,5	38	500
2	70	500
3	140	500
4	280	500
5	390	250
6	550	200
8	900	200
10	1230	200
12	1700	200
14	2000	150
16	3700	100

Colours Ø 1-5 mm (NF)

	525 Black
	526 Blue
	527 Green
	530 Red
	536 Yellow
	539 Orange
	541 Grey
	543 Brown

Colours Ø 6-16 mm

	010 Blue
	059 Yellow
	086 Green
	150 Orange
	171 Red
	188 Black
	541 Grey NF
	543 Brown NF



Material
spun-dyed
Polypropylene multifilament

Construction
8-plaited

LIROS Nautic Hollow Braid 01072

All-purpose spun-dyed Polypropylene multifilament. Very easy to splice, floats. 16-plaited hollow braid.

- working stretch < 15%
- very easy to splice
- durable and UV stabilised

Reference	Ø mm	Breaking strength kg	Length of spool m
01072-0900	9	1000	200
01072-1012	11	1300	200



Colours

	525 Black		530 Red		542 White
	526 Blue		536 Yellow		543 Brown
	527 Green				

Material spun-dyed Polypropylene multifilament

Construction 16-plaited without core



8-plaited

Spiral braid

LIROLEN Braid
01070 / E1070 / 01075


High-strength Polypropylene multifilament, good UV resistance, floats.

- working stretch < 12%
- UV-stabilised
- custom lengths available

Construction 01070

Ø 1 – 16mm
1 mm 6-plaited
2 mm and up 8-plaited

Colour 01070



Construction E1070

Ø 2 – 16mm
16-plaited with core


Colour E1070



Construction 01075

Ø 3 – 16mm
spiral braid

Colour 01075



Material
high-tenacity
Polypropylene
multifilament

Ø mm	Breaking strength kg 01070/E1070	Breaking strength kg 01075	Length of spool m
1	30	–	500
2	75	–	500
3	140	90	500
4	280	140	500
5	390	200	250
6	550	310	200
8	1000	600	200
10	1300	1100	200
12	1600	1700	200
14	2000	2000	150
16	3300	2600	100



LIROS All-Purpose **01060 / 01061**

Economical, floating all-purpose line in UV-stabilised Polypropylene fibres.

Colour 01060



Colour 01061



Ø mm	Breaking strength kg	Length of spool m
6	400	200
8	700	200
10	1100	200
12	1500	200

Material 01060 Polypropylene monofilament
Material 01061 Polypropylene split-fibre

Construction 8-plaited



LIROS Venetian Blind Cord 20140 / 20145 22140 / 22145

100% Polyester from 2.5 mm with core, tight braided. UV- and abrasion resistant.

- *round, dimensionally stable braid*
- *custom lengths and colours available*

Reference	Ø mm	Length of spool m
20140 / 22140	0,8	500
	1	500
	1,5	500
	1,7	500
20145 / 22145 (with core)	2	500
	2,5	500
	3	500
	3,5	500

Colour 20140 / 20145
 228
 White

Colour 22140 / 22145
 188
 Black




Material high-tenacity Polyester **Construction** 16-plaited with core


LIROS Starter Cord 10145 / 10445

Special twist and compact braid construction for extreme abrasion resistance. 100% Polyamide. Durable and high stretch to minimise recoil.

- *special impregnation upon request (Ref. 10445)*
- *custom lengths available*

Ø mm	Length of spool m
3	500
3,5	500
4	500
4,5	500
5	250
6	200

Colour 10145
 228
 White

Colour 10445
 418
 White, impregnated



Material high-strength Polyamide **Construction** 16-plaited without core



LIROS Trim Line

01051

Low-stretch, high-grip, great holding power in cleats. Compact, round, UV- and abrasion resistant braiding.

- working stretch < 5 %
- low-stretch, high-grip
- excellent for windsurfing

Colours



188
Black



229
White-Blue




Material
Polyester

Construction
16-plaited with twisted core

Ø mm	Breaking strength kg	Length of spool m
3	200	100
4	320	100
4,5	500	100
5	610	100
6	800	100

INDUSTRY



LIROS All-purpose Line

10070 / 10072

For camping, outdoor, around the house. Handy winder pre-packed in LIROS polybag.

- attractive, selfservice product
- UV resistant
- multiple outdoor and industrial applications

Reference	Ø mm	Winder length m
10070/10072-0230	3	20
10070/10072-0330	3	30
10070/10072-0530	3	50
10070/10072-0240	4	20
10070/10072-0340	4	30
10070/10072-0250	5	20
10070/10072-0350	5	30

Colour 10070



228
White

Colours 10072



010
Blue



059
Yellow



086
Green



171
Red



188
Black



Material Polypropylene multifilament

Construction 8-plaited




LIROS Barrier Color

01160 / 01161

Visually appealing cable braid, specially designed for stairways and cordoned areas.

- Ø 28-30mm
- *custom lengths available*

Colours 01160



Colour 01161



Material 01160 Acrylic yarn
Material 01161 Spun Polyester

Construction
4-strand cable braiding



LIROS Barrier Classic

1140D / 0114D

Cable braided rope, specially designed for stairways and cordoned areas. Polyhemp has the same good grip as hemp, but is even softer and more weather-resistant.

- *abrasion resistant*
- *easy to splice*

Colour



Material 1140D
spun Polypropylene rope yarn

Material 0114D
natural spun hemp

Construction
4-strand cable twist



LIROS Barrier Classic

01141

Cable braided rope, specially designed for stairways and cordoned areas. Polyhemp has the same good grip as hemp, but is even softer and more weather-resistant.

- *Diameter 35 mm*
- *100m coil*

Colour



Material
spun Polypropylene rope yarn

Construction
4-strand cable twist





LIROS Seastar Classic

00173

Premium high-grip, natural-coloured cover-core sheet for traditional yachts.

- working stretch < 6%
- high-grip, easy to handle
- high-end, classic look
- available with low-stretch Dyneema® core for racing applications (Ref. 02520)

Colour



546
Hemp NF

Cover

matt Polyester yarn

Construction

6 – 8mm	16-plaited
10 – 12mm	20-plaited
14mm and up	24-plaited

Core

high-tenacity braided Polyester

Ø mm	Breaking strength kg	Length of spool m
6	520	200
8	1000	200
10	1900	200
12	2400	200
14	2900	150
16	3500	100
18	4500	100
20	5200	100



TRADITIONAL



LIROS Classic 3-strand

01172

Premium high-grip, natural-coloured 3-strand rope for traditional yachts. Durable and abrasion resistant.

- working stretch > 15%
- high-grip, very easy to handle
- premium appearance

Colour



546
Hemp NF

Material

matt Polyester yarn

Construction

3-strand



Ø mm	Breaking strength kg	Length of spool m
3	100	250
4	170	250
5	250	250
6	350	200
8	730	200
10	1100	200
12	1300	200
14	1700	150
16	2200	100
18	3500	100
20	4900	100



LIROS ClassTech

01127

LIROS ClassTech is the ideal line for classic sailors with ambition. Combines the high abrasion resistance and durability of synthetic fibres with the classic look of hemp ropes.

- working stretch > 8%
- durable and UV stabilised
- acid- and base-resistant
- very abrasion resistant
- spliceable
- floatable
- only available in 220m coils

Colour



705
Beige NF

Material high-tenacity Polypropylene fibre

Construction 3-strand

Ø mm	Breaking strength kg	Length of coil m
10	1600	220
12	2250	220
14	3100	220
16	3850	220
18	4900	220
20	5900	220
22	7100	220
24	8300	220
26	9550	220
28	10900	220
32	13750	220



LIROS Historic

01140

Looks like hemp, but softer, more weather-resistant, and better durability, UV resistant.

- working stretch > 15%
- easy to splice
- soft, good grip
- classic appearance
- weather-resistant
- floatable

Colour



546
Hemp NF

Material spun Polypropylene yarn

Construction 3-strand

Ø mm	Breaking strength kg	Length of spool m
6	320	200
8	500	200
10	800	200
12	1100	200
14	1500	150
16	2000	100
18	2400	100
20	3000	100
22	3650	100
24	4800	100
26	5400	100
28	6000	100
30	6400	50





LIROS Hemp Cord

00310

100% flax for a classic appearance.

- Perfect for decorative applications
- environmentally friendly
- naturally bio-degrades

Colour



546
Hemp NF



Ø mm	Length of spool m
3	500
3,5	500
4	500
4,5	500
5	250
6	200
8	200
10	200
12	200
14	150
16	100

Material

Flax

Construction

8-plaited



LIROS Hemp Rope

00114

100% natural hemp, according to **DIN EN 1261** (previously DIN 83325).

- high grip
- environmentally friendly
- naturally bio-degrades

Colour



546
Hemp NF

Ø mm	Breaking strength kg	Length of spool m
6	285	200
8	450	200
10	700	200
12	1080	200
14	1375	150
16	1825	100
18	2250	100
20	2780	100
22	3240	100
24	3980	100

Material

Natural hemp

Construction

6mm 3-strand
8mm and up 4-strand





8-plaited

16-plaited

LIROS Cotton Cord

00510 / 00512

100% natural cotton.

- soft and high grip
- environmentally friendly
- naturally bio-degrades

Ø mm	Length of spool m
3	500
4	500
5	250
6	200
8	200
10	200

8-plaited



16-plaited without core



Material
Cotton

Construction 00510
8-plaited

Construction 00512
16-plaited
available in Ø 2-12 mm

LIROS Sisal Rope

00113

100% natural, cropped sisal.

- compact
- environmentally friendly
- naturally bio-degrades

Ø mm	Breaking strength kg	Length of spool m
6	310	200
8	425	200
10	560	200
12	840	200
14	1100	150
16	1490	100

Colour



Material
Sisal

Construction
6mm 3-strand
8mm and up 4-strand





LIROS Rigger Bag

00146-0056

Premium splicing kit for the professional sailor. Contains all the splicing tools and accessories needed to work on all known LIROS yachting rope types.

- *ext. dimensions: 41x31x10cm*
- *Contains: 1x Whipping needle; 1x swedish fid; 3x splicing needles (5,5-7,5-10mm); LIROS rope catalogue; 1x scissor; LIROS USB-Stick with splicing instructions; LIROS Tape; Dyneema® whipping twine; 1x pen; 1x lighter*

LIROS Protect

Perfect protection for mooring lines up to 30 mm diameter. To be fixed with or without wire ties for flexible adjustment at the rope.

- *width 37 mm for ropes up to 16mm*
- *width 60 mm for ropes from 18mm up to 30mm diameter*
- *LIROS Protect is available in pieces or provided on reels*

Reference	Ø mm	for rope Ø	Length m
00146-0272	37	8-16	50 (spool)
00146-0273	37	8-16	2x0,75 (kit incl. cable ties)
00146-0274	60	18-30	50 (spool)
00146-0275	60	18-30	2x0,75 (kit incl. cable ties)





LIROS Splicer Pro

00143

The professional tool for our LIROS splicing department – ideal for all core-cover splices.

Reference	Size	Splice mm*	Measurements mm
00143-1000	S	4–8	180x6
00143-2000	M	10–12	300x8
00143-3000	L	12–14	335x9
00143-3050	XL	16–20	260x12
00143-5008	XXL	22–28	500x18

*depends on the rope plait



LIROS Splicing Needle Set 00143

Five premium stainless steel splicing needles, perfect for splicing ropes from 4–14 mm in diameter. Suitable for twisted and for plaited lines. Comes in a convenient plastic tube with screw-top.

- Measurements: 233 x 12,5mm; 175 x 9mm; 115 x 7mm; 135 x 5mm

Reference	Size	Content	for rope Ø mm
00143-5004	Standard	set of 4	4–14mm
00143-5011	Dinghy	set of 2	4–6mm
00143-5012	Cruising	set of 2	8–14mm



LIROS Whipping Needle

00143-4000

LIROS Splicing Department-approved needle for splicing and whipping lines up to 4mm. Usable without sailmaker gloves. Saves time and energy while whipping any kind of rope.



LIROS Swedish Fid

00143

Classic, reliable splicing tool for 3-strand and square-braided ropes.

- 00143-0005 – up to 12mm
- 00143-0006 – 14mm and up

LIROS Micro-Splicing Needle 00143-4001

Ideal for splicing hollow braided kite and paragliding lines from 0,6mm up to 1,1 mm. 6 pieces per package.



LIROS Connect

00104

Extremely safe – extremely easy – extremely strong.
A high-quality alternative to common forest winch attachments. Simply loop your rope around LIROS Connect and attach your hook for a professional installation. Can be done by any user directly on-site.



Reference	00104-0001	00104-0002
Rope diameter	10mm	12-16mm
Max. load	5t	10t
Pin diameter:	16,5mm	21,5mm
Distance between end plates	50mm	57mm
End plate diameter	36,5mm	53,5mm



Usage example (rope and hook not included)

LIROS XTR-Finish

00146-0057

LIROS XTR-Finish is the perfect coating for additional protection against abrasion and UV effects on all kind of ropes (Polyester, Dyneema®, Zylon®). LIROS XTR-Finish comes in 250ml bottles.

- ready to use
- optimized UV-protection
- easy-to-clean, water-based solution
- each package: 250ml bottle + sponge
- available colours: 010 Blue, 059 Yellow, 078 Grey, 086 Green, 171 Red, 220 Transparent





LIROS Heat Cutter 00146

Cutting and sealing synthetic ropes and lines. 21 mm cutting edge.

- 60W rating
- for adult use only
- 00146-0000 Heat cutter
- 00146-0001 Replacement blade



LIROS Heat Cutter Pro 00146

For professional use. Cutting and sealing of synthetic ropes and lines. 40mm cutting edge. Quick setup and cutting edge heating.

- 120 W rating
- for adult use only
- 00146-0276 Heat Cutter Pro
- 00146-0018 Replacement blade



LIROS Heat Cutter Cordless 00146

- 115W rating
- ideal for mobile use
- quick setup and cutting edge heating
- 00146-0284 Heat Cutter Pro
- 00146-0001 Replacement blade



LIROS Scissor Pro 00146-0277

Specially designed to cut Dyneema®, Vectran®, Aramid, PBO. Micro-serrated.

- total length 16 cm
- cutting length 3 cm
- for adult use only

LIROS Ceramic Pro 00146-0278

Top quality riggers knife for clean dry cuts. Perfect for cutting Dyneema®, Vectran®, Aramid, PBO.

- blade length: 11 cm
- razor sharp
- rust resistant
- very lightweight





LIROS Splicing Bench 00146-0106

Professional splicing bench designed by LIROS to provide perfect working conditions for professional splicing and rigging. Features Antal-W48ST aluminium winch for pretensioning ropes. Special LIROS anchor point for making eye splices.

- (l) 2,00m x (w) 0,80m x (h) 1,20m
- also available without winch
- with detailed fid-length stencil for optimal splice lengths



LIROS Rope Measuring Gauge 00138

00138

High quality and robust construction. For plaited cords, plaited lines and ropes with diameters between 3mm and 20mm. For wall mounting.

- size: 43 x 26cm
- weight: 2,9 kg

LIROS Rope Display

00135

Premium free-standing or wall-mount rope display. Guarantee for superior presentation of LIROS rope. Premium powdercoated brush metal appearance.

Reference	Description	pieces required for one free-standing display	pieces required for one wall display
00135-3001	Side element (175 cm height)	4	2
00135-3002	Extension (80 cm height)	(4)	(2)
00135-3003	Top for headline (25 cm height)	4	2
00135-3004	Bars (92 cm width)	12	6
00135-3005	Reinforcement braces (2-piece)	1	-
00135-3006	Advertising sign (92 cm width/ 25 cm height)	2	1

SHOP DISPLAYS





LIROS Infoboard

00135-3012

LIROS Infoboard ensures optimal presentation of LIROS products at the point of sale. The detailed, individual description of each LIROS rope product facilitates and supports the salesperson on site. Fits LIROS Rope display.


Contents:

- 1x Infoboard
- 2x self-adhesive marking strips
- 1x cover sheet for product cards
- 1x rubber cord 105 cm
- 1x fitting instructions
- width: 90 cm/ depth: 43 cm
(exceeding the bars by 26 cm)

LIROS Cutting Plate **00135-3015**

Variable fixable cutting plate. Includes two hooks for hanging the heat cutting device, scissors, etc. Keeps order on LIROS Rope Displays.

- *Measurements: (w) 13cm x (d) 37cm*



LIROS Counter Display

00146-0016

Premium silver powder-coated metal display for optimal presentation at the point of sale.

Can be fitted with 4 sales packages e.g. Magic Sport, Trimline or whipping twine (see page 47-50).

- *Colour Silver*



LIROS Flag

Reference	Measurements
00146-0099	80 x 80 cm
00146-0032	160 x 160 cm
00146-0028	150 x 300 cm
00146-0204	150 x 400 cm



LIROS Coffee Cup 00146-0029



LIROS Backpack

High quality LIROS backpack with a storage capacity of 20 litres.

- one large main + two side compartments
- padded back
- adjustable shoulder straps and chest strap

Reference	Capacity L
-----------	---------------

00146-0318	20
------------	----



LIROS Fleece Vest

Made of Polyester, sizes from S to 3XL.



LIROS Sticker

Reference	Measurements
-----------	--------------

①	00146-0047	Ø 50 cm
②	00146-0052	Ø 25 cm
③	00146-0110	30 x 7 cm
④	00146-0046	80 x 12 cm
⑤	00146-0048	Ø 9 cm

LIROS Canvas Sticker

Reference	Measurements
-----------	--------------

⑥	00146-0216	Ø 40 cm
⑦	00146-0205	Ø 25 cm
⑧	00146-0215	Ø 20 cm
	00146-0214	Ø 15 cm



LIROS Carpet

Premium LIROS doormat.
Easy to clean.

Reference	Measurements
-----------	--------------

00146-0075	60 x 40 cm
00146-0040	85 x 120 cm

LIROS Drinks bottle 00146-0325

High quality thermal drinks bottle, made from stainless steel. Capacity: 0,75L.



Recommended Line Diameters

Regatta

sail surface (m ²)	10	20	30	40	50	60	70	80	90	100
Racer-XTR 02008	–	–	8	8	8	10	10	12	12	14
Racer Hybrid 02026	–	–	8	8	8	10	10	12	12	14
Racer Vision 02027	–	–	8	8	8	10	10	12	12	14
Racer 02001	–	6	8	10	10	12	12	14	14	16
Regatta 02000	5	6	8	10	10	12	12	14	14	16
Dynamic 02004/02028	6	8	10	12	14	14	14	–	–	–
D-Pro 01505/01508	4	5	6	8	8	9	9	10	12	14
Control-XTR 02024/02224	5	6	8	8	8	10	10	12	12	14
V-Force 04000	6	8	8	10	12	–	–	–	–	–

Cruising

sail surface (m ²)	10	20	30	40	50	60	70	80	90	100
Racer 02001	–	6	8	10	10	12	12	14	14	16
Regatta 02000	5	6	8	10	10	12	12	14	14	16
Dynamic 02004/02028	6	8	10	12	12	14	14	–	–	–
TopGrip 01540	6	8	10	12	14	14	14	–	–	–
Herkules 00154/01550/01552	6	8	10	12	14	14	14	16	16	18
Top-Cruising 00152/01528	6	8	10	12	14	14	14	16	16	18
Prestretch 00121/00122	6	8	10	12	–	–	–	–	–	–
Allround 00151	8	10	12	14	14	16	–	–	–	–
Seastar 00162/00172	6	8	10	12	14	14	16	18	18	–

For guy ropes, choose a heavier diameter



Always choose the right stopper based on your line's diameter.
The wrong stopper size can damage your line.

Recommended Mooring Lines



Mooring Lines

	Boat Size (ft)	20–27	33	40	46	52–60	65–73	78–85	90–105	110–118	124–131
	Boat Size (m)	6–8	10	12	14	16–18	20–22	24–26	28–32	34–36	38–40
	Displacement (t)	<1	2	5	12	20	25	30	40	70	>80
catalogue		Ø mm	Ø mm	Ø mm	Ø mm	Ø mm	Ø mm	Ø mm	Ø mm	Ø mm	Ø mm
22	Super Yacht Mooring 01300	–	–	–	–	–	–	–	24	24	28
24	Porto 00133	10	12	14	16	18	20	22	24	–	–
25	Squareline 01047/01049	10	12	14	16	18	20	22	24	26	28
27	PES-3-strand 00111/01110	10	12	14	16	18	20	22	24	26	28
26	Holiday 01083	12	14	16	–	–	–	–	–	–	–
26	Moorex 12 00132	12	14	16	18	20	22	24	26	28	30
29	Latina 00110	10	12	14	16	18	20	22	22	24	26
23	Handy Elastic 00136/00137	10	12	14	16	18	20	22	22	24	26



Always secure any watercraft with at least 4 mooring lines.
Length of lines: Two lines @ 1.5x boat-length and two lines @ 1.0x boat-length (m)

INFO

LIROS manufactures materials, which are subject to customary fluctuations. All published technical data are therefore only for general reference and comply with the average results achieved in the manufacturing process. Alterations in design, technology and manufacture are subject to change at any time.

We recommend visual inspection of every line, before and after use. Lines should be removed from use if the load-bearing portion shows evidence of damage, even through normal wear and tear.

Please find safety instructions for LIROS ropes on www.liros.com/support/technical-informationen

LIROS products for personal safety and for lifting loads are specially labelled. Technical specifications are not binding and do not set the customer free from his duty to check if the products are suitable for the intended operation and purpose.

LIROS splices are guaranteed up to 80% of the stated linear breaking load!!


Please find splicing instructions for LIROS ropes on www.liros.com/support/downloads

Care instructions: LIROS quality lines may be washed in mild detergent on „delicate“ cycle at 30°C, packed in a cotton bag.


CRUISING

	page
1. Main halyard	
LIROS Regatta 2000	17
LIROS Dynamic	18
LIROS Herkules	20
LIROS Taper Pro	41
2. Genoa halyard	
LIROS Regatta 2000	17
LIROS Dynamic	18
3. Spinnaker halyard	
LIROS Dynamic	18
LIROS Herkules	20
LIROS Magic Pro	36
4. Boom topping lift	
LIROS Herkules	20
LIROS Top Cruising	22
LIROS Magic Sport	38
5. Pole topping lift (not shown)	
LIROS Herkules	20
LIROS Top Cruising	22
6. Pole downhaul (not shown)	
LIROS Dynamic	18
LIROS Herkules	20
LIROS Top Cruising	22
7. Genoa sheet	
LIROS Herkules	20
LIROS Top Grip	21
LIROS Top Cruising	22
LIROS Seastar	23
LIROS Magic Sport	38
8. Main sheet	
LIROS Top Grip	21
LIROS Top Cruising	22
LIROS Seastar	23
LIROS Magic Sheet	38
LIROS Magic Sport	38
9. Boomvang	
LIROS Herkules	20
LIROS Top Cruising	22
LIROS Magic Sheet	38
10. Spinnaker sheet (not shown)	
LIROS Top Grip	21
LIROS Top Cruising Color	22
LIROS Allround	23
LIROS Seastar	23
LIROS Magic Sheet	38
LIROS Magic Sport	38
11. Backstay/running backstay	
LIROS Dynamic	18
LIROS Herkules	20
LIROS Magic Sheet	38
12. Cunningham	
LIROS Top Cruising Color	22
LIROS Top Cruising	22
LIROS Magic Sport	38
13. Outhaul	
LIROS Herkules	20
LIROS Top Cruising	22

LIROS usage recommendations



Cruising boat



Racing boat

Our recommendations for LIROS items reflect our many years' experience racing and cruising.

Source: Hanse Yachts / Judel Vrolijk

REGATTA


	page
1. Main halyard	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS Racer Vision	15
LIROS Racer	16
LIROS Regatta 2000	17
LIROS Control XTR	11
2. Genoa halyard	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS Racer Vision	15
LIROS Racer	16
LIROS V-Force	16
LIROS Regatta 2000	17
3. Spinnaker halyard	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS Racer	16
LIROS Dynamic	18
4. Pole topping lift	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS V-Force	16
LIROS Dynamic	18
LIROS Regatta 2000	17
5. Pole downhaul	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS Racer	16
6. Genoa sheet	
LIROS Racer-XTR	12
LIROS Racer Hybrid	15
LIROS Racer	16
LIROS Regatta 2000	17
7. Spinnaker sheet	
LIROS Racer	16
LIROS Dynamic	18
LIROS Control-XTR	11
LIROS Magic Edge	36
LIROS Dynasoft	37
8. Guy	
LIROS Racer Vision	15
LIROS V-Force	16
9. Main sheet	
LIROS Racer	16
LIROS Dynamic	18
LIROS Magic Pro	36
LIROS Dynasoft	37
10. Backstay/running backstay	
LIROS V-Force	16
LIROS Regatta 2000	17
LIROS D-Pro-XTR	12
LIROS D-Pro Static	13
11. Cunningham	
LIROS Racer	16
LIROS Regatta 2000	17
LIROS D-Pro	19
12. Outhaul	
LIROS V-Force	16
LIROS Regatta 2000	17
LIROS D-Pro	19
LIROS Magic Edge	36
13. Boomvang	
LIROS Racer	16
LIROS Dynamic	18
LIROS D-Pro	19
LIROS V-Plus-XTR	13
LIROS Magic Pro	36
14. Boom topping lift (not shown)	
LIROS Dynamic	18






Performance

Cruising



- LIROS V-Force, LIROS V-Plus
- LIROS D-Pro, D-Pro Vision
- LIROS Racer Vision, LIROS Racer Hybrid
- LIROS Racer, LIROS Regatta 2000
- LIROS Dynamic Color
- LIROS Dynasoft
- LIROS Herkules/Herkules Color/Herkules Vision, LIROS Top Grip, LIROS Top Cruising, LIROS Top Cruising Color
- LIROS Seastar
- LIROS Prestretch
- LIROS Allround, LIROS Standard
- LIROS Nautic


Mooring



- LIROS Squareline PP, LIROS Polyestertauwerk, LIROS Nautic
- LIROS Polyamidtauwerk
- LIROS Porto, LIROS Super Yacht Mooring
- LIROS Moorex 12, LIROS Holiday
- LIROS Squareline Polyester
- LIROS Handy-Elastic

Magic Dinghy Performance

Magic













- LIROS Magic XTR, LIROS Magic Control XTR
- LIROS D-Pro, LIROS D-Pro Vision
- LIROS Magic Pro, LIROS Magic Race
- LIROS Magic Edge
- LIROS Magic Sport, LIROS Spi
- LIROS Magic Sheet

Comparing summary of synthetic fibres

Material		Polyamid (PA) 6 and 6,6		Polyester (PES)		Polypropylene (PP) multifilament high-strength		Polyethylene high-strength (HMPE)		Aramid		LCP		PBO	
Brand	Perlon Nylon						Dyneema® Spectra®			Twaron® Kevlar® Technora®			Vectran®		Zylon®
Yarn strength															
cN/dtex	7 – 8	7 – 9	6 – 7	28 – 40	20 – 25	22 – 25	ca. 37								
Specific weight															
kg/dm³	1,14	1,38	0,91	0,96	1,44	1,41	1,52								
Strength loss due to humidity															
%	5 – 10	0	0	0	0	0	0								
Water absorption															
%	1 – 7	0,5 – 2	0	0	2 – 5	1	0,6								
Knot tenacity (residual value breaking strength)															
%	60 – 65	55 – 60	55 – 65	35 – 50	30 – 40	30 – 35	35 – 55								
Light resistance															
	good	very good	adequate	very good	poor	adequate	poor								
Breaking stretch															
%	16 – 27	10 – 16	12 – 20	2 – 3	2 – 4	2 – 3	2,5								
Abrasion resistance	very good	very good	fair	very good	adequate	very good	adequate								

PERFORMANCE

Reaction of synthetic ropes under different conditions

Material							
	Polyamide (PA) 6 / 6,6	Polyester (PES)	Polypropylene (PP)	Polyethylene (PE, HMPE)	Aramid	LCP	PBO
Brand	Perlon Nylon			Dyneema® Spectra®	Twaron® Kevlar® Technora®	Vectran®	Zylon®
 Washing temp. °C	40	40	30	30	60	60	60
 Acids (50% concentr.) 25 °C / 100 °C Rest %	17 / 5-10	80 / 0	no reaction	no reaction	good resistance	very good resistance	good resistance
 Gasoline	no reaction	no reaction	no reaction	no reaction	no reaction	no reaction	no reaction
 Diesel and Oil	no reaction	no reaction	no reaction	no reaction	no reaction	no reaction	no reaction
 Solvents	minimal reaction	minimal reaction	minimal reaction	minimal reaction	minimal reaction	minimal reaction	minimal reaction
 Alkalien (Leaches)	resistant against weak alkalis	resistant against weak alkalis at 20 °C	resistant against weak alkalis	resistant	resistant against weak alkalis	resistant	resistant
 Insulating properties	good (when dry)	excellent	excellent	excellent	good (when dry)	excellent	excellent
 Highest temp. Short load approx. °C	130	170	80	70	400	200	550
 Range Exposure approx. °C	170	225	140	120	-	-	-
 Melting point approx. °C	215	260	170	150	chars at approx. 500 °C	330	chars at approx. 650 °C



LIROS GmbH

Sieggrubenstraße 7
D-95180 Berg

Tel.: +49 (0) 92 93 / 80 02 0

www.liros.com · info@liros.com

